

DEPARTMENT OF COMMERCE
National Bureau of Standards

NBS SPECIAL PUBLICATION 330
1981 EDITION

THE INTERNATIONAL SYSTEM OF UNITS (SI)



NATIONAL BUREAU OF STANDARDS

The National Bureau of Standards¹ was established by an act of Congress on March 3, 1901. The Bureau's overall goal is to strengthen and advance the Nation's science and technology and facilitate their effective application for public benefit. To this end, the Bureau conducts research and provides: (1) a basis for the Nation's physical measurement system, (2) scientific and technological services for industry and government, (3) a technical basis for equity in trade, and (4) technical services to promote public safety. The Bureau's technical work is performed by the National Measurement Laboratory, the National Engineering Laboratory, and the Institute for Computer Sciences and Technology.

THE NATIONAL MEASUREMENT LABORATORY provides the national system of physical and chemical and materials measurement; coordinates the system with measurement systems of other nations and furnishes essential services leading to accurate and uniform physical and chemical measurement throughout the Nation's scientific community, industry, and commerce; conducts materials research leading to improved methods of measurement, standards, and data on the properties of materials needed by industry, commerce, educational institutions, and Government; provides advisory and research services to other Government agencies; develops, produces, and distributes Standard Reference Materials; and provides calibration services. The Laboratory consists of the following centers:

Absolute Physical Quantities² — Radiation Research — Thermodynamics and Molecular Science — Analytical Chemistry — Materials Science.

THE NATIONAL ENGINEERING LABORATORY provides technology and technical services to the public and private sectors to address national needs and to solve national problems; conducts research in engineering and applied science in support of these efforts; builds and maintains competence in the necessary disciplines required to carry out this research and technical service; develops engineering data and measurement capabilities; provides engineering measurement traceability services; develops test methods and proposes engineering standards and code changes; develops and proposes new engineering practices; and develops and improves mechanisms to transfer results of its research to the ultimate user. The Laboratory consists of the following centers:

Applied Mathematics — Electronics and Electrical Engineering² — Mechanical Engineering and Process Technology² — Building Technology — Fire Research — Consumer Product Technology — Field Methods.

THE INSTITUTE FOR COMPUTER SCIENCES AND TECHNOLOGY conducts research and provides scientific and technical services to aid Federal agencies in the selection, acquisition, application, and use of computer technology to improve effectiveness and economy in Government operations in accordance with Public Law 89-306 (40 U.S.C. 759), relevant Executive Orders, and other directives; carries out this mission by managing the Federal Information Processing Standards Program, developing Federal ADP standards guidelines, and managing Federal participation in ADP voluntary standardization activities; provides scientific and technological advisory services and assistance to Federal agencies; and provides the technical foundation for computer-related policies of the Federal Government. The Institute consists of the following centers:

Programming Science and Technology — Computer Systems Engineering.

¹Headquarters and Laboratories at Gaithersburg, MD, unless otherwise noted; mailing address Washington, DC 20234.

²Some divisions within the center are located at Boulder, CO 80303.

THE INTERNATIONAL SYSTEM OF UNITS (SI)

Edited by

David T. Goldman
National Bureau of Standards
United States of America

R. J. Bell
National Physical Laboratory
United Kingdom

(Translation approved by the
International Bureau of Weights and
Measures of its publication "Le Système
International d'Unités")

(Supersedes NBS Special Publication 330
1977 Edition)



U.S. DEPARTMENT OF COMMERCE, Malcolm Baldrige, Secretary

NATIONAL BUREAU OF STANDARDS, Ernest Ambler, Director

Issued December 1981

National Bureau of Standards Special Publication 330

Nat. Bur. Stand. (U.S.), Spec. Publ. 330, 53 pages (Dec. 1981)

CODEN: NBSMA6

U.S. GOVERNMENT PRINTING OFFICE

WASHINGTON: 1981

For sale by the Superintendent of Documents, U.S. Government Printing Office, Washington, D.C. 20402

Price \$3.25


(Add 25 percent for other than U.S. mailing)

Foreword

Le Bureau International des Poids et Mesures welcomes with pleasure the appearance of this booklet, an English translation of the new edition of the brochure, "Le Système International d'Unités (SI)," published in French by the BIPM.* The translation was a joint effort by the National Bureau of Standards (USA) and the National Physical Laboratory (UK). It was checked by the BIPM, found to conform with the original both in letter and spirit, and approved.

SI, the present-day descendant of the Metric System, has become the universal language of scientists. It is becoming the universal language of measurement in all industrial, technical, and commercial areas; in all branches of human activity; and in all countries.

This publication provides for all English-speaking users a complete documentation and a careful updating of the foundations and fundamental principles of SI. It will contribute to a better understanding, to a better dissemination, and to a more uniformly correct utilization of SI. It is one more step towards a mutual understanding between peoples.

A handwritten signature in black ink, appearing to read 'P. Giacomo', with a large, stylized flourish above the name.

P. Giacomo, Director, BIPM

* "Le Système International d'Unités," 4th edition (1981), agent: OFFILIB, 48 rue Gay-Lussac, F-75005 Paris. Complete or partial translations (of this and/or former editions) have been published in Bulgarian, Chinese, Czechoslovakian, English, German, Japanese, Romanian, Portuguese, and Spanish. Numerous countries have also published guides for the utilization of SI units.

Preface to the 4th Edition

The International Bureau of Weights and Measures (BIPM), in response to frequent requests, publishes this document containing Resolutions and Recommendations of the General Conference on Weights and Measures (CGPM) and the International Committee for Weights and Measures (CIPM) on the International System of Units. Explanations have been added as well as relevant extracts from the International Standards of the International Organization for Standardization (ISO) for the practical use of the System.

The Consultative Committee for Units (CCU) of the International Committee for Weights and Measures (CIPM) helped to draft the document and has approved the final text.

Appendix I reproduces in chronological order the decisions (Resolutions, Recommendations, Declarations, etc.) promulgated since 1889 by the CGPM and the CIPM on units of measurement and on the International System of Units.

Appendix II outlines the measurements, consistent with the theoretical definitions given here, which metrological laboratories can make to realize the units and to calibrate precision material standards.

This 4th edition is a revision of the 3d edition (1977); it takes into consideration the decisions of the 16th General Conference on Weights and Measures (1979) and of the International Committee for Weights and Measures (1977, 1978, 1980), and the amendments made by the Consultative Committee for Units (1978, 1980).

January 1981

P. GIACOMO
Director, BIPM

J. de BOER
Chairman, CCU

The International System of Units

Contents

	Page
Foreword.....	iii
Preface to the 4th Edition	iv
I. Introduction.....	1
I.1 Historical note.....	1
I.2 Three classes of SI units.....	1
I.3 SI prefixes.....	2
I.4 System of quantities.....	2
I.5 Legislation on units.....	2
II. SI units	3
II.1 SI base units.....	3
II.1.1. Definitions.....	3
II.1.2. Symbols	6
II.2 SI derived units.....	6
II.3 SI supplementary units	9
II.4 Rules for writing and using SI unit symbols.....	10
III. Decimal multiples and sub-multiples of SI units.....	11
III.1 SI prefixes.....	11
III.2 Rules for using SI prefixes	11
III.3 The kilogram	12
IV. Units outside the International System	13
IV.1 Units used with the International System	13
IV.2 Units in use temporarily	14
IV.3 CGS units	15
IV.4 Other units.....	16
Appendix I. Decisions of the CGPM and the CIPM.....	17
Appendix II. Practical realization of the definitions of some important units.....	39
Appendix III. Organs of the Meter Convention.....	44
Index	47

I. INTRODUCTION

I.1 Historical note

In 1948 the 9th CGPM[†], by its Resolution 6, instructed the CIPM:[†] “to study the establishment of a complete set of rules for units of measurement”; “to find out for this purpose, by official inquiry, the opinion prevailing in scientific, technical, and educational circles in all countries” and “to make recommendations on the establishment of a *practical system of units of measurement* suitable for adoption by all signatories to the Meter Convention.”

The same General Conference also laid down, by its Resolution 7, general principles for unit symbols and also gave a list of units with special names.

The 10th CGPM (1954), by its Resolution 6, and the 14th CGPM (1971) by its Resolution 3, adopted as base units of this “practical system of units,” the units of the following seven quantities: length, mass, time, electric current, thermodynamic temperature, amount of substance, and luminous intensity.

The 11th CGPM (1960), by its Resolution 12, adopted the name *International System of Units*, with the international abbreviation, SI, for this practical system of units of measurement, and laid down rules for the prefixes, the derived and supplementary units, and other matters, thus establishing a comprehensive specification for units of measurement.

I.2 The three classes of SI units

SI units are divided into three classes: *base* units, *derived* units, and *supplementary* units.

From the scientific point of view, division of SI units into these three classes is to a certain extent arbitrary, because it is not essential to the physics of the subject.

Nevertheless, the General Conference, considering the advantages of a single, practical, worldwide system for international relations, for teaching, and for scientific work, decided to base the International System on a choice of seven well-defined units which by convention are regarded as dimensionally independent: the meter, the kilogram, the second, the ampere, the kelvin, the mole, and the candela (see II.1, p. 3). These SI units are called *base units*.

The second class of SI units contains *derived units*; i.e., units that can be formed by combining base units according to the algebraic relations linking the corresponding quantities. The names and symbols of some units thus formed in terms of base units can be replaced by special names and symbols which can themselves be used to form expressions and symbols of other derived units (see II.2, p. 6).

The 11th CGPM (1960) admitted a third class of SI units, called *supplementary units*, whose nature was not stated exactly (see II.3, p. 9).

[†] For the meaning of these abbreviations, see the preface.

The SI units of these three classes form a coherent set of units in the sense normally attributed to the word "coherent"; i.e., a system of units mutually related by rules of multiplication and division without any numerical factor. Following CIPM Recommendation 1 (1969), the units of this coherent set of units are designated by the name *SI units*.

It is important to emphasize that each physical quantity has only one SI unit, even if this unit can be expressed in different forms, but the inverse is not true: the same SI unit can correspond to several different quantities (see p. 8).

I.3 The SI prefixes

The General Conference has adopted a series of prefixes to be used in forming the decimal multiples and submultiples of SI units (see III.1, p. 11). Following CIPM Recommendation 1 (1969), the set of prefixes is designated by the name *SI prefixes*.

The multiples and submultiples of SI units, which are formed by using the SI prefixes, should be designated by their complete name, *multiples and submultiples of SI units*, in order to make a distinction between them and the coherent set of SI units proper.

I.4 System of quantities

This booklet does not deal with the system of quantities used with the SI units, an area handled by Technical Committee 12 of the *International Organization for Standardization (ISO)* which, since 1955, has published a series of International Standards on quantities and their units, and which strongly recommends the use of the International System of Units.¹

In these International Standards, ISO has adopted a system of physical quantities based on the seven base quantities: length, mass, time, electric current, thermodynamic temperature, amount of substance, and luminous intensity. The other quantities—the derived quantities—are defined in terms of these seven base quantities; the relationships between the derived quantities and the base quantities are expressed by a system of equations. It is this system of quantities and equations that is properly used with the SI units.

I.5 Legislation on units

Countries have established, through legislation, rules concerning the use of units on a national basis, either for general use, or for specific areas such as commerce, health or public safety, and education. In a growing number of countries this legislation is based on the use of the International System of Units.

The *International Organization of Legal Metrology (OIML)*, founded in 1955, is concerned with the international harmonization of this legislation.

¹ Units of measurement, ISO Standards Handbook 2, ISO, Geneva, 1979, 235 pages.

II. SI UNITS

II.1 SI base units

II.1.1. Definitions

(a) unit of
length
(meter)

The 11th CGPM (1960) replaced the definition of the meter based on the international prototype of platinum-iridium, in force since 1889 and amplified in 1927, by the following definition:

The meter is the length equal to 1 650 763.73 wavelengths in vacuum of the radiation corresponding to the transition between the levels $2p_{10}$ and $5d_5$ of the krypton-86 atom. (11th CGPM (1960), Resolution 6).

The old international prototype of the meter which was legalized by the 1st CGPM in 1889 is still kept at the International Bureau of Weights and Measures under the conditions specified in 1889.

(b) unit of
mass
(kilogram)

The 1st CGPM (1889) legalized the international prototype of the kilogram and declared: *this prototype shall henceforth be considered to be the unit of mass.*

The 3d CGPM (1901), in a declaration intended to end the ambiguity which existed as to the meaning of the word “weight” in popular usage, confirmed that *the kilogram is the unit of mass; it is equal to the mass of the international prototype of the kilogram* (see the complete declaration, p. 18).

This international prototype made of platinum-iridium is kept at the BIPM under conditions specified by the 1st CGPM in 1889.

(c) unit of
time
(second)

The unit of time, the second, was defined originally as the fraction $1/86\,400$ of the mean solar day. The exact definition of “mean solar day” was left to astronomers, but their measurements have shown that on account of irregularities in the rotation of Earth, the mean solar day does not guarantee the desired accuracy. In order to define the unit of time more precisely the 11th CGPM (1960) adopted a definition given by the International Astronomical Union which was based on the tropical year. Experimental work had, however, already shown that an atomic standard of time-interval, based on a transition between two energy levels of an atom or a molecule, could be realized and reproduced much more accurately. Considering that a very precise definition of the unit of time of the International System, the second, is indispensable for the needs of advanced metrology, the 13th CGPM (1967) decided to replace the definition of the second by the following:

The second is the duration of 9 192 631 770 periods of the radiation corresponding to the transition between the two hyperfine levels of the ground state of the cesium-133 atom. (13th CGPM (1967), Resolution 1).

(d) unit of
electric
current
(ampere)

Electric units, called “international,” for current and resistance, had been introduced by the International Electrical Congress held in Chicago in 1893, and the definitions of the “international” ampere and the “international” ohm were confirmed by the International Conference of London in 1908.

Although it was already obvious on the occasion of the 8th CGPM (1933) that there was a unanimous desire to replace those “international” units by so-called

“absolute” units, the official decision to abolish them was only taken by the 9th CGPM (1948), which adopted for the unit of electric current, the ampere, the following definition:

The ampere is that constant current which, if maintained in two straight parallel conductors of infinite length, of negligible circular cross section, and placed 1 meter apart in vacuum, would produce between these conductors a force equal to 2×10^{-7} newton per meter of length. (CIPM (1946), Resolution 2 approved by the 9th CGPM, 1948).

The expression “MKS unit of force” which occurs in the original text has been replaced here by “newton,” the name adopted for this unit by the 9th CGPM (1948, Resolution 7).

(e) unit of
thermo-
dynamic
temper-
ature
(kelvin)

The definition of the unit of thermodynamic temperature was given in substance by the 10th CGPM (1954, Resolution 3) which selected the triple point of water as the fundamental fixed point and assigned to it the temperature 273.16 K by definition. The 13th CGPM (1967, Resolution 3) adopted the name *kelvin* (symbol K) instead of “degree Kelvin” (symbol °K) and in its Resolution 4 defined the unit of thermodynamic temperature as follows:

The kelvin, unit of thermodynamic temperature, is the fraction $1/273.16$ of the thermodynamic temperature of the triple point of water. (13th CGPM (1967), Resolution 4).

The 13th CGPM (1967, Resolution 3) also decided that the unit kelvin and its symbol K should be used to express an interval or a difference of temperature.

Note: In addition to the thermodynamic temperature (symbol T), expressed in kelvins, use is also made of Celsius temperature (symbol t) defined by the equation

$$t = T - T_0$$

where $T_0 = 273.15$ K by definition. To express Celsius temperature, the unit “degree Celsius” which is equal to the unit “kelvin” is used; in this case, “degree Celsius” is a special name used in place of “kelvin.” An interval or difference of Celsius temperature can, however, be expressed in kelvins as well as in degrees Celsius.

(f) unit of
amount of
substance
(mole)

Since the discovery of the fundamental laws of chemistry, units of amount of substance called, for instance, “gram-atom” and “gram-molecule,” have been used to specify amounts of chemical elements or compounds. These units had a direct connection with “atomic weights” and “molecular weights,” which were in fact relative masses. “Atomic weights” were originally referred to the atomic weight of oxygen (by general agreement taken as 16). But whereas physicists separated isotopes in the mass spectrograph and attributed the value 16 to one of the isotopes of oxygen, chemists attributed that same value to the (slightly variable) mixture of isotopes 16, 17, 18, which was for them the naturally occurring element oxygen. Finally an agreement between the International Union of Pure and Applied Physics (IUPAP) and the International Union of Pure and Applied Chemistry (IUPAC) brought this duality to an end in 1959/60. Physicists and chemists have ever since agreed to assign the value 12 to the isotope 12 of carbon. The unified scale thus obtained gives values of “relative atomic mass.”

It remained to define the unit of amount of substance by fixing the corresponding mass of carbon 12; by international agreement, this mass has been fixed at 0.012 kg, and the unit of the quantity, "amount of substance,"² has been given the name *mole* (symbol mol).

Following proposals of IUPAP, IUPAC, and ISO, the CIPM gave in 1967, and confirmed in 1969, the following definition of the mole, adopted by the 14th CGPM (1971, Resolution 3):

1. *The mole is the amount of substance of a system that contains as many elementary entities as there are atoms in 0.012 kilogram of carbon 12.*
2. *When the mole is used, the elementary entities must be specified and may be atoms, molecules, ions, electrons, other particles, or specified groups of such particles.*

In the definition of the mole, it is understood that unbound atoms of carbon 12, at rest and in their ground state, are referred to.

Note that this definition specifies at the same time the nature of the quantity whose unit is mole.

**(g) unit of
luminous
intensity
(candela)**

The units of luminous intensity based on flame or incandescent filament standards in use in various countries before 1948 were replaced initially by the "new candle" based on the luminance of a Planckian radiator (a blackbody) at the temperature of freezing platinum. This decision had been prepared by the International Commission on Illumination (CIE) and by the International Committee for Weights and Measures before 1937, and was promulgated by the CIPM in 1946, and then ratified in 1948 by the 9th CGPM which adopted a new international name for this unit, the *candela* (symbol cd); in 1967 the 13th CGPM gave an amended version of the 1946 definition.

Because of the experimental difficulties in realizing a Planck radiator at high temperatures and the new possibilities offered by radiometry, i.e. the measurement of optical radiation power, the 16th CGPM adopted in 1979 the following new definition:

The candela is the luminous intensity, in a given direction, of a source that emits monochromatic radiation of frequency 540×10^{12} hertz and that has a radiant intensity in that direction of (1/683) watt per steradian. (16th CGPM (1979), Resolution 3).

² The name of this quantity, adopted by IUPAP, IUPAC, and ISO is in French "quantité de matière" and in English "amount of substance"; (the German and Russian translations are "Stoffmenge" and "количество вещества"). The French name recalls "quantitas materiae" by which in the past the quantity now called mass used to be known; we must forget this old meaning, for mass and amount of substance are entirely different quantities.

II.1.2. Symbols

The base units of the International System are collected in table 1 with their names and their symbols (10th CGPM (1954), Resolution 6; 11th CGPM (1960), Resolution 12; 13th CGPM (1967), Resolution 3; 14th CGPM (1971), Resolution 3).

TABLE 1
SI base units

Quantity [†]	SI Unit	
	Name	Symbol
length	meter	m
mass	kilogram	kg
time	second	s
electric current	ampere	A
thermodynamic temperature	kelvin	K
amount of substance	mole	mol
luminous intensity	candela	cd

[†] Translators' note: "Quantity" is the technical word for measurable attributes of phenomena or matter.

II.2 SI derived units

Derived units are expressed algebraically in terms of base units by means of the mathematical symbols of multiplication and division (see table 2 for some examples).

TABLE 2
Examples of SI derived units expressed in terms of base units

Quantity	SI Unit	
	Name	Symbol
area	square meter	m ²
volume	cubic meter	m ³
speed, velocity	meter per second	m/s
acceleration	meter per second squared	m/s ²
wave number	1 per meter	m ⁻¹
density, mass density	kilogram per cubic meter	kg/m ³
specific volume	cubic meter per kilogram	m ³ /kg
current density	ampere per square meter	A/m ²
magnetic field strength	ampere per meter	A/m
concentration (of amount of substance)	mole per cubic meter	mol/m ³
luminance	candela per square meter	cd/m ²

Certain derived units have been given special names and symbols. These names and symbols are given in tables 3 and 3'; they may themselves be used to express other derived units (see table 4 for some examples).

TABLE 3
SI derived units with special names

Quantity	SI Unit			
	Name	Symbol	Expression in terms of other units	Expression in terms of SI base units
frequency	hertz	Hz		s^{-1}
force	newton	N		$m \cdot kg \cdot s^{-2}$
pressure, stress	pascal	Pa	N/m^2	$m^{-1} \cdot kg \cdot s^{-2}$
energy, work, quantity of heat	joule	J	$N \cdot m$	$m^2 \cdot kg \cdot s^{-2}$
power, radiant flux	watt	W	J/s	$m^2 \cdot kg \cdot s^{-3}$
electric charge, quantity of electricity	coulomb	C		$s \cdot A$
electric potential, potential difference, electromotive force	volt	V	W/A	$m^2 \cdot kg \cdot s^{-3} \cdot A^{-1}$
capacitance	farad	F	C/V	$m^{-2} \cdot kg^{-1} \cdot s^4 \cdot A^2$
electric resistance	ohm	Ω	V/A	$m^2 \cdot kg \cdot s^{-3} \cdot A^{-2}$
electric conductance	siemens	S	A/V	$m^{-2} \cdot kg^{-1} \cdot s^3 \cdot A^2$
magnetic flux	weber	Wb	$V \cdot s$	$m^2 \cdot kg \cdot s^{-2} \cdot A^{-1}$
magnetic flux density	tesla	T	Wb/m^2	$kg \cdot s^{-2} \cdot A^{-1}$
inductance	henry	H	Wb/A	$m^2 \cdot kg \cdot s^{-2} \cdot A^{-2}$
Celsius temperature ^(a)	degree Celsius	$^{\circ}C$		K
luminous flux	lumen	lm		$cd \cdot sr^{(b)}$
illuminance	lux	lx	lm/m^2	$m^{-2} \cdot cd \cdot sr^{(b)}$

^(a) See page 4, e, Note.

^(b) See II.3, page 9, and CIPM, 1980, Recommendation 1, page 38.

TABLE 3'
SI derived units with special names admitted for reasons of safeguarding human health

Quantity	SI Unit			
	Name	Symbol	Expression in terms of other units	Expression in terms of SI base units
activity (of a radionuclide)	becquerel	Bq		s^{-1}
absorbed dose, specific energy imparted, kerma, absorbed dose index	gray	Gy	J/kg	$m^2 \cdot s^{-2}$
dose equivalent, dose equivalent index	sievert	Sv	J/kg	$m^2 \cdot s^{-2}$

TABLE 4

Examples of SI derived units expressed by means of special names

Quantity	SI Unit		
	Name	Symbol	Expression in terms of SI base units
dynamic viscosity	pascal second	Pa·s	$\text{m}^{-1} \cdot \text{kg} \cdot \text{s}^{-1}$
moment of force	newton meter	N·m	$\text{m}^2 \cdot \text{kg} \cdot \text{s}^{-2}$
surface tension	newton per meter	N/m	$\text{kg} \cdot \text{s}^{-2}$
heat flux density, irradiance	watt per square meter	W/m ²	$\text{kg} \cdot \text{s}^{-3}$
heat capacity, entropy	joule per kelvin	J/K	$\text{m}^2 \cdot \text{kg} \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
specific heat capacity, specific entropy	joule per kilogram kelvin	J/(kg·K)	$\text{m}^2 \cdot \text{s}^{-2} \cdot \text{K}^{-1}$
specific energy	joule per kilogram	J/kg	$\text{m}^2 \cdot \text{s}^{-2}$
thermal conductivity	watt per meter kelvin	W/(m·K)	$\text{m} \cdot \text{kg} \cdot \text{s}^{-3} \cdot \text{K}^{-1}$
energy density	joule per cubic meter	J/m ³	$\text{m}^{-1} \cdot \text{kg} \cdot \text{s}^{-2}$
electric field strength	volt per meter	V/m	$\text{m} \cdot \text{kg} \cdot \text{s}^{-3} \cdot \text{A}^{-1}$
electric charge density	coulomb per cubic meter	C/m ³	$\text{m}^{-3} \cdot \text{s} \cdot \text{A}$
electric flux density	coulomb per square meter	C/m ²	$\text{m}^{-2} \cdot \text{s} \cdot \text{A}$
permittivity	farad per meter	F/m	$\text{m}^{-3} \cdot \text{kg}^{-1} \cdot \text{s}^4 \cdot \text{A}^2$
permeability	henry per meter	H/m	$\text{m} \cdot \text{kg} \cdot \text{s}^{-2} \cdot \text{A}^{-2}$
molar energy	joule per mole	J/mol	$\text{m}^2 \cdot \text{kg} \cdot \text{s}^{-2} \cdot \text{mol}^{-1}$
molar entropy, molar heat capacity	joule per mole kelvin	J/(mol·K)	$\text{m}^2 \cdot \text{kg} \cdot \text{s}^{-2} \cdot \text{K}^{-1} \cdot \text{mol}^{-1}$
exposure (x and γ rays)	coulomb per kilogram	C/kg	$\text{kg}^{-1} \cdot \text{s} \cdot \text{A}$
absorbed dose rate	gray per second	Gy/s	$\text{m}^2 \cdot \text{s}^{-3}$

As mentioned at the end of section I.2 (p. 2), the same SI unit can correspond to several different quantities; some examples are given in the tables above, where the enumeration of the cited quantities should not be considered exhaustive. The name of the unit is thus not sufficient to define the quantity measured; in particular, measuring instruments should indicate not only the unit but also the measured quantity concerned.

Although a derived unit can be expressed in several equivalent ways by using names of base units and special names of derived units, the CIPM sees no objection to the use of certain combinations or of certain special names in order to distinguish more easily between quantities of the same dimension. For example, the hertz is used, instead of the reciprocal second, for frequency; and the newton meter, instead of the joule, for moment of force.

In the field of ionizing radiation, the becquerel is similarly used, instead of the reciprocal second, for activity; and the gray or the sievert, instead of the joule per kilogram, for their respective quantities.

Note: The values of certain so-called dimensionless quantities, as for example refractive index, relative permeability, or relative permittivity, are expressed by pure numbers. The corresponding SI unit is then the ratio of two identical SI units and may be expressed by the number 1.

II.3 SI supplementary units

This class contains two units: the SI unit of plane angle, the *radian*, and the SI unit of solid angle, the *steradian* (11th CGPM (1960), Resolution 12).

TABLE 5
SI supplementary units

Quantity	SI unit	
	Name	Symbol
plane angle	radian	rad
solid angle	steradian	sr

At the time of the introduction of the International System, the 11th CGPM left open the question of the nature of these supplementary units. Considering that plane angle is generally expressed as the ratio between two lengths and solid angle as the ratio between an area and the square of a length, the CIPM (1980) specified that in the International System the quantities plane angle and solid angle should be considered as dimensionless derived quantities. Therefore, the supplementary units radian and steradian are to be regarded as dimensionless derived units which may be used or omitted in the expressions for derived units.

Some examples of the use of supplementary units in forming derived units are given in table 6.

TABLE 6
Examples of SI derived units formed by using supplementary units

Quantity	SI unit	
	Name	Symbol
angular velocity	radian per second	rad/s
angular acceleration	radian per second squared	rad/s ²
radiant intensity	watt per steradian	W/sr
radiance	watt per square meter steradian	W·m ⁻² ·sr ⁻¹

II.4 Rules for writing and using SI unit symbols

The general principles concerning writing the unit symbols were adopted by the 9th CGPM (1948, Resolution 7):

1. Roman (upright) type, in general lower case, is used for the unit symbols. If, however, the name of the unit is derived from a proper name, the first letter of the symbol is in upper case.
2. Unit symbols are unaltered in the plural.
3. Unit symbols are not followed by a period.

To insure uniformity in the use of the SI unit symbols, ISO International Standards give certain recommendations. Following these recommendations:

- a) The product of two or more units may be indicated in any of the following ways,[†]

for example: $\text{N}\cdot\text{m}$, N.m , or N m .

- b) A solidus (oblique stroke, /), a horizontal line, or negative exponents may be used to express a derived unit formed from two others by division,

for example: m/s , $\frac{\text{m}}{\text{s}}$ or $\text{m}\cdot\text{s}^{-1}$

- c) The solidus must not be repeated on the same line unless ambiguity is avoided by parentheses. In complicated cases negative exponents or parentheses should be used,

for example: m/s^2 or $\text{m}\cdot\text{s}^{-2}$ *but not:* m/s/s
 $\text{m}\cdot\text{kg}/(\text{s}^3\cdot\text{A})$ or $\text{m}\cdot\text{kg}\cdot\text{s}^{-3}\cdot\text{A}^{-1}$ $\text{m}\cdot\text{kg/s}^3/\text{A}$

[†] USA Editors' note: For USA practice, see American National Standard ANSI/IEEE Std 260-1978.

III. DECIMAL MULTIPLES AND SUB-MULTIPLES OF SI UNITS

III.1 SI prefixes

The 11th CGPM (1960, Resolution 12) adopted a first series of prefixes and symbols of prefixes to form the names and symbols of the decimal multiples and submultiples of SI units. Prefixes for 10^{-15} and 10^{-18} were added by the 12th CGPM (1964, Resolution 8) and those for 10^{15} and 10^{18} by the 15th CGPM (1975, Resolution 10).

TABLE 7

SI prefixes

Factor	Prefix	Symbol	Factor	Prefix	Symbol
10^{18}	exa	E	10^{-1}	deci	d
10^{15}	peta	P	10^{-2}	centi	c
10^{12}	tera	T	10^{-3}	milli	m
10^9	giga	G	10^{-6}	micro	μ
10^6	mega	M	10^{-9}	nano	n
10^3	kilo	k	10^{-12}	pico	p
10^2	hecto	h	10^{-15}	femto	f
10^1	deka	da	10^{-18}	atto	a

III.2 Rules for using SI prefixes

Following the general principles adopted by the ISO, the CIPM recommends that the following rules for using the SI prefixes be observed:

1. Prefix symbols are printed in roman (upright) type without spacing between the prefix symbol and the unit symbol.
2. The grouping formed by the prefix symbol attached to the unit symbol constitutes a new inseparable symbol (of a multiple or submultiple of the unit concerned) which can be raised to a positive or negative power and which can be combined with other unit symbols to form compound unit symbols,

for example:

$$\begin{aligned}
 1 \text{ cm}^3 &= (10^{-2} \text{ m})^3 = 10^{-6} \text{ m}^3 \\
 1 \text{ cm}^{-1} &= (10^{-2} \text{ m})^{-1} = 10^2 \text{ m}^{-1} \\
 1 \mu\text{s}^{-1} &= (10^{-6} \text{ s})^{-1} = 10^6 \text{ s}^{-1} \\
 1 \text{ V/cm} &= (1 \text{ V})/(10^{-2} \text{ m}) = 10^2 \text{ V/m}
 \end{aligned}$$

3. Compound prefixes, i.e., prefixes formed by the juxtaposition of two or more SI prefixes, are not to be used,

for example: 1 nm *but not:* 1 m μ m

4. A prefix should never be used alone

for example: $10^6/\text{m}^3$ *but not:* M/m³

III.3 The kilogram

Among the base units of the International System, the unit of mass is the only one whose name, for historical reasons, contains a prefix. Names of decimal multiples and sub-multiples of the unit of mass are formed by attaching prefixes to the word “gram” (CIPM (1967), Recommendation 2),

for example: $10^{-6} \text{ kg} = 1 \text{ milligram (1 mg)}$ *but not:* 1 microkilogram ($1 \mu\text{kg}$).

IV. UNITS OUTSIDE THE INTERNATIONAL SYSTEM

IV.1 Units used with the International System

The CIPM (1969) recognized that users of SI will wish to employ with it certain units not part of it, but which are important and are widely used. These units are given in table 8. The combination of units of this table with SI units to form compound units should be restricted to special uses in order not to lose the advantage of the coherence of SI units.

TABLE 8
Units in use with the International System

Name	Symbol	Value in SI unit
minute	min	1 min = 60 s
hour ^(a)	h	1 h = 60 min = 3 600 s
day	d	1 d = 24 h = 86 400 s
degree	°	1° = ($\pi/180$) rad
minute	'	1' = (1/60)° = ($\pi/10\,800$) rad
second	"	1" = (1/60)' = ($\pi/648\,000$) rad
liter ^(b)	l, L	1 L = 1 dm ³ = 10 ⁻³ m ³
metric ton ^{(c)†}	t	1 t = 10 ³ kg

^(a) The symbol of this unit is included in Resolution 7 of the 9th CGPM (1948).

^(b) This unit and the symbol l were adopted by CIPM in 1879 (*Procès-Verbaux CIPM*, 1879, p. 41). The alternative symbol, L, was adopted by the 16th CGPM (1979, Resolution 6) in order to avoid the risk of confusion between the letter l and the number 1.[†] The present definition of the liter is in Resolution 6 of the 12th CGPM (1964).

^(c) This unit and its symbol were adopted by the International Committee in 1879 (*Procès-Verbaux CIPM*, 1879, p. 41).

It is likewise necessary to recognize, outside the International System, some other units that are useful in specialized fields, because their values expressed in SI units must be obtained by experiment, and are therefore not known exactly (table 9).

TABLE 9
*Units used with the International System whose values
in SI units are obtained experimentally*

Name	Symbol	Definition
electronvolt	eV	^(a)
unified atomic mass unit	u	^(b)

^(a) The electronvolt is the kinetic energy acquired by an electron in passing through a potential difference of 1 volt in vacuum; 1 eV = $1.602\,19 \times 10^{-19}$ J approximately.

^(b) The unified atomic mass unit is equal to (1/12) of the mass of an atom of the nuclide ¹²C; 1 u = $1.660\,57 \times 10^{-27}$ kg approximately.

[†] Translators' note: In some English-speaking countries this unit is called "tonne."

[†] USA Editors' note: In the USA, the recommended symbol for liter is L.

IV.2 Units in use temporarily

In view of existing practice in certain fields or countries, the CIPM (1978) considered that it was acceptable for those units listed in table 10 to continue to be used with SI units until the CIPM considers their use no longer necessary. However, these units should not be introduced where they are not used at present.

TABLE 10
Units in use temporarily with the International System

Name	Symbol	Value in SI unit
nautical mile ^(a)		1 nautical mile = 1 852 m
knot		1 nautical mile per hour = (1852/3600) m/s
ångström	Å	1 Å = 0.1 nm = 10 ⁻¹⁰ m
are ^(b)	a	1 a = 1 dam ² = 10 ² m ²
hectare ^(b)	ha	1 ha = 1 hm ² = 10 ⁴ m ²
barn ^(c)	b	1 b = 100 fm ² = 10 ⁻²⁸ m ²
bar ^(d)	bar	1 bar = 0.1 MPa = 10 ⁵ Pa
gal ^(e)	Gal	1 Gal = 1 cm/s ² = 10 ⁻² m/s ²
curie ^(f)	Ci	1 Ci = 3.7 × 10 ¹⁰ Bq
roentgen ^(g)	R	1 R = 2.58 × 10 ⁻⁴ C/kg
rad ^(h)	rad	1 rad = 1 cGy = 10 ⁻² Gy
rem ⁽ⁱ⁾	rem	1 rem = 1 cSv = 10 ⁻² Sv

^(a) The nautical mile is a special unit employed for marine and aerial navigation to express distances. The conventional value given above was adopted by the First International Extraordinary Hydrographic Conference, Monaco, 1929, under the name "International nautical mile."

^(b) This unit[†] and its symbol were adopted by the CIPM in 1879 (*Procès-Verbaux CIPM*, 1879, p. 41).

^(c) The barn is a special unit employed in nuclear physics to express effective cross sections.

^(d) This unit and its symbol are included in Resolution 7 of the 9th CGPM (1948).

^(e) The gal is a special unit employed in geodesy and geophysics to express the acceleration due to gravity.

^(f) The curie is a special unit employed in nuclear physics to express activity of radionuclides (12th CGPM (1964), Resolution 7).

^(g) The roentgen is a special unit employed to express exposure of x or γ radiations.

^(h) The rad is a special unit employed to express absorbed dose of ionizing radiations. When there is risk of confusion with the symbol for radian, rd may be used as the symbol for rad.

⁽ⁱ⁾ The rem is a special unit used in radioprotection to express dose equivalent.

[†] USA Editors' note: In recommended USA practice, hectare would appear in table 8.

IV.3 CGS units

In the field of mechanics, the CGS system of units was based upon three base units: the centimeter, the gram, and the second. In the field of electricity and magnetism, units were expressed in terms of these three base units; this led to the establishment of several different systems, for example the CGS Electrostatic System, the CGS Electromagnetic System, and the CGS Gaussian System. In these three last mentioned systems, the system of quantities and the corresponding system of equations are often different from those used with SI units.

The CIPM considers that it is in general preferable not to use, with the units of the International System, CGS units that have special names.³ Such units are listed in table 11.

TABLE 11
CGS units with special names

Name	Symbol	Value in SI unit
erg ^(a)	erg	1 erg = 10 ⁻⁷ J
dyne ^(a)	dyn	1 dyn = 10 ⁻⁵ N
poise ^(a)	P	1 P = 1 dyn·s/cm ² = 0.1 Pa·s
stokes	St	1 St = 1 cm ² /s = 10 ⁻⁴ m ² /s
gauss ^(b)	Gs, G	1 Gs corresponds to 10 ⁻⁴ T
oersted ^(b)	Oe	1 Oe corresponds to $\frac{1000}{4\pi}$ A/m
maxwell ^(b)	Mx	1 Mx corresponds to 10 ⁻⁸ Wb
stilb ^(a)	sb	1 sb = 1 cd/cm ² = 10 ⁴ cd/m ²
phot	ph	1 ph = 10 ⁴ lx

^(a) This unit and its symbol were included in Resolution 7 of the 9th CGPM (1948).

^(b) This unit is part of the so-called "electromagnetic" 3-dimensional CGS system and cannot strictly speaking be compared to the corresponding unit of the International System, which has four dimensions when only mechanical and electric quantities are considered.

³ The aim of the International System of Units and of the recommendations contained in this document is to secure a greater degree of uniformity, hence a better mutual understanding of the general use of units. Nevertheless in certain specialized fields of scientific research, in particular in theoretical physics, there may sometimes be very good reasons for using other systems or other units.

Whichever units are used, it is important that the *symbols* employed for them follow current international recommendations.

IV.4 Other units

As regards units outside the International System which do not come under sections IV.1, 2, and 3, the CIPM considers that it is in general preferable to avoid them, and to use instead units of the International System. Some of those units are listed in table 12.

TABLE 12
Other units generally deprecated

Name	Value in SI unit
fermi	1 fermi = 1 fm = 10^{-15} m
metric carat ^(a)	1 metric carat = 200 mg = 2×10^{-4} kg
torr	1 torr = $\frac{101\,325}{760}$ Pa
standard atmosphere (atm) ^(b)	1 atm = 101 325 Pa
kilogram-force (kgf)	1 kgf = 9.806 65 N
calorie (cal) ^(c)	
micron (μ) ^(d)	1 μ = 1 μ m = 10^{-6} m
x unit ^(e)	
stere (st) ^(f)	1 st = 1 m ³
gamma (γ)	1 γ = 1 nT = 10^{-9} T
γ ^(g)	1 γ = 1 μ g = 10^{-9} kg
λ ^(h)	1 λ = 1 μ L = 10^{-6} L = 10^{-9} m ³

^(a) This name was adopted by the 4th CGPM (1907, pp. 89-91) for commercial dealings in diamonds, pearls, and precious stones.

^(b) Resolution 4 of the 10th CGPM (1954). The designation "standard atmosphere" for a reference pressure of 101 325 Pa is still acceptable.

^(c) Several "calories" have been in use:

— calorie labeled "at 15 °C": 1 cal₁₅ = 4.185 5 J (value adopted by the CIPM in 1950 (*Procès-Verbaux CIPM*, 22, 1950, pp. 79-80));

— a calorie labeled "IT" (International Table): 1 cal_{IT} = 4.186 8 J (5th International Conference on the Properties of Steam, London, 1956);

— a calorie labeled "thermochemical": 1 cal_{th} = 4.184 J.

^(d) The name of this unit and its symbol, adopted by the CIPM in 1879 (*Procès-Verbaux CIPM*, 1879, p. 41) and retained in Resolution 7 of the 9th CGPM (1948) were abolished by the 13th CGPM (1967, Resolution 7).

^(e) This special unit was employed to express wavelengths of x rays; 1 x unit = 1.002×10^{-4} nm approximately.

^(f) This special unit employed to measure firewood was adopted by the CIPM in 1879 with the symbol "s" (*Procès-Verbaux CIPM*, 1879, p. 41). The 9th CGPM (1948, Resolution 7) changed the symbol to "st."

^(g) This symbol is mentioned in *Procès-Verbaux CIPM*, 1880, p. 56.

^(h) This symbol is mentioned in *Procès-Verbaux CIPM*, 1880, p. 30.

APPENDIX I

Decisions of the CGPM and the CIPM

The more important decisions abrogated, modified, or added to, are indicated by an asterisk (*). These references and the footnotes have been added by the BIPM to make understanding of the text easier.

CR: *Comptes rendus des séances de la Conférence Générale des Poids et Mesures (CGPM)*

PV: *Procès-Verbaux des séances du Comité International des Poids et Mesures (CIPM)*

1st CGPM, 1889

meter
kilogram

Sanction of the international prototypes of the meter and the kilogram (CR, 34-38)

The General Conference

considering

the “Compte rendu of the President of the CIPM” and the “Report of the CIPM,” which show that, by the collaboration of the French section of the international Meter Commission and of the CIPM, the fundamental measurements of the international and national prototypes of the meter and of the kilogram have been made with all the accuracy and reliability that the present state of science permits; that the international and national prototypes of the meter and the kilogram are made of an alloy of platinum with 10 percent iridium, to within 0.000 1; the equality in length of the international Meter and the equality in mass of the international Kilogram with the length of the Meter and the mass of the Kilogram kept in the Archives of France;

that the differences between the national Meters and the international Meter lie within 0.01 millimeter and that these differences are based on a hydrogen thermometer scale which can always be reproduced thanks to the stability of hydrogen, provided identical conditions are secured;

that the differences between the national Kilograms and the international Kilogram lie within 1 milligram;

that the international Meter and Kilogram and the national Meters and Kilograms fulfil the requirements of the Meter Convention,

sanctions

A. As regards international prototypes:

1 The Prototype of the meter chosen by the CIPM. This prototype, at the temperature of melting ice, shall henceforth represent the metric unit of length.*
.....

* Definition abrogated in 1960 (see p. 25: 11th CGPM, Resolution 6).

2 The Prototype of the kilogram adopted by the CIPM. This prototype shall henceforth be considered as the unit of mass.

3 The hydrogen thermometer centigrade scale in terms of which the equations of the prototype Meters have been established.

B. As regards national prototypes:

3d CGPM, 1901

liter

Declaration concerning the definition of the liter (CR, 38)

.....

The Conference declares:

1 The unit of volume, for high accuracy determinations, is the volume occupied by a mass of 1 kilogram of pure water, at its maximum density and at standard atmospheric pressure; this volume is called "liter."*

2.....

* Definition abrogated in 1964 (see p. 29: 12th CGPM, Resolution 6)

mass and
weight
 g_n

Declaration on the unit of mass and on the definition of weight; conventional value of g_n (CR, 70)

Taking into account the decision of the CIPM of the 15 October 1887, according to which the kilogram has been defined as a unit of mass;⁴

Taking into account the decision contained in the sanction of the prototypes of the Metric System, unanimously accepted by the CGPM on the 26 September 1889;

Considering the necessity to put an end to the ambiguity which in current practice still subsists on the meaning of the word *weight*, used sometimes for *mass*, sometimes for *mechanical force*;

The Conference declares:

"1 The kilogram is the unit of mass; it is equal to the mass of the international prototype of the kilogram;

"2 The word *weight*[†] denotes a quantity of the same nature as a *force*; the weight of a body is the product of its mass and the acceleration due to gravity; in particular, the standard weight of a body is the product of its mass and the standard acceleration due to gravity;

[†] USA Editors' note: In the USA, ambiguity exists in the use of the term weight as a quantity to mean either force or mass. In science and technology this declaration (CGPM (1901)) is usually followed, with the newton the corresponding unit. In commercial and everyday use, weight is often used in the sense of mass for which the SI unit is the kilogram.

"3 The value adopted in the international Service of Weights and Measures for the standard acceleration due to gravity is 980.665 cm/s^2 , value already stated in the laws of some countries."⁵

⁴ "The mass of the international Kilogram is taken as the unit for the international Service of Weights and Measures" (PV, 1887, 88).

⁵ This conventional reference "standard value" ($g_n = 9.806 65 \text{ m/s}^2$) was confirmed in 1913 by the 5th CGPM (CR, 44). This value should be used for reduction to standard gravity of measurements made in any location on Earth.

meter

Definition of the meter by the international Prototype (CR, 49)

The unit of length is the meter, defined by the distance, at 0°, between the axes of the two central lines marked on the bar of platinum-iridium kept at the BIPM, and declared Prototype of the meter by the 1st CGPM, this bar being subject to standard atmospheric pressure and supported on two cylinders of at least one centimeter diameter, symmetrically placed in the same horizontal plane at a distance of 571 mm from each other.*

* Definition abrogated in 1960 (see p. 25: 11th CGPM, Resolution 6).

CIPM, 1946

photometric
units*Definitions of photometric units (PV, 20, 119)*RESOLUTION⁶

.....

4. The photometric units may be defined as follows:

New candle (unit of luminous intensity).—The value of the new candle is such that the brightness of the full radiator at the temperature of solidification of platinum is 60 new candles per square centimeter.*

New lumen (unit of luminous flux).—The new lumen is the luminous flux emitted in unit solid angle (steradian) by an isotropic point source having a luminous intensity of 1 new candle.

5.

* Definition modified in 1967 (see p. 31: 13th CGPM, Resolution 5).

mechanical
and
electric
units*Definitions of electric units (PV, 20, 131)*RESOLUTION 2⁷

.....

4. A) Definitions of the mechanical units which enter the definitions of electric units:

Unit of force.—The unit of force [in the MKS (Meter, Kilogram, Second) system] is that force which gives to a mass of 1 kilogram an acceleration of 1 meter per second, per second.

Joule (unit of energy or work).—The joule is the work done when the point of application of 1 MKS unit of force [newton] moves a distance of 1 meter in the direction of the force.

⁶ The two definitions contained in this Resolution were ratified by the 9th CGPM (1948), which also approved the name *candela* given to the “new candle” (CR, 54). For the lumen the qualifier “new” was later abandoned.

⁷ The definitions contained in this Resolution 2 were approved by the 9th CGPM (1948), (CR, 49), which moreover adopted the name *newton* (Resolution 7) for the MKS unit of force.

Watt (unit of power).—The watt is the power which in one second gives rise to energy of 1 joule.

B) Definitions of electric units. The CIPM accepts the following propositions which define the theoretical value of the electric units:

Ampere (unit of electric current).—The ampere is that constant current which, if maintained in two straight parallel conductors of infinite length, of negligible circular cross-section, and placed 1 meter apart in vacuum, would produce between these conductors a force equal to 2×10^{-7} MKS unit of force [newton] per meter of length.

Volt (unit of potential difference and of electromotive force).—The volt is the difference of electric potential between two points of a conducting wire carrying a constant current of 1 ampere, when the power dissipated between these points is equal to 1 watt.

Ohm (unit of electric resistance).—The ohm is the electric resistance between two points of a conductor when a constant potential difference of 1 volt, applied to these points, produces in the conductor a current of 1 ampere, the conductor not being the seat of any electromotive force.

Coulomb (unit of quantity of electricity).—The coulomb is the quantity of electricity carried in 1 second by a current of 1 ampere.

Farad (unit of electric capacitance).—The farad is the capacitance of a capacitor between the plates of which there appears a potential difference of 1 volt when it is charged by a quantity of electricity of 1 coulomb.

Henry (unit of electric inductance).—The henry is the inductance of a closed circuit in which an electromotive force of 1 volt is produced when the electric current in the circuit varies uniformly at the rate of 1 ampere per second.

Weber (unit of magnetic flux).—The weber is that magnetic flux which, linking a circuit of one turn, would produce in it an electromotive force of 1 volt if it were reduced to zero at a uniform rate in 1 second.

9th CGPM, 1948

thermo-
dynamic
scale
unit of
quantity of
heat

Triple point of water; thermodynamic scale with a single fixed point; unit of quantity of heat (joule) (CR, 55 and 63)

RESOLUTION 3⁸

1. With present-day technique, the triple point of water is capable of providing a thermometric reference point with an accuracy higher than can be obtained from the melting point of ice.

In consequence the Consultative Committee [for Thermometry and Calorimetry] considers that the zero of the centesimal thermodynamic scale must be defined as the temperature 0.010 0 degree below that of the triple point of pure water.

⁸ The three propositions contained in this Resolution 3 have been adopted by the General Conference.

2. The CCTC accepts the principle of an absolute thermodynamic scale with a single fundamental fixed point at present provided by the triple point of pure water, the absolute temperature of which will be fixed at a later date.

The introduction of this new scale does not affect in any way the use of the International Scale, which remains the recommended practical scale.

3. The unit of quantity of heat is the joule.

Note: It is requested that the results of calorimetric experiments be as far as possible expressed in joules.

If the experiments are made by comparison with the rise of temperature of water (and that, for some reason, it is not possible to avoid using the calorie), the information necessary for conversion to joules must be provided.

The CIPM, advised by the CCTC, should prepare a table giving, in joules per degree, the most accurate values that can be obtained from experiments on the specific heat of water.⁹

degree
Celsius

Adoption of "degree Celsius"

From three names ("degree centigrade," "centesimal degree," "degree Celsius") proposed to denote the degree of temperature, the CIPM has chosen "degree Celsius" (PV, 21, 1948, 88).

This name is also adopted by the General Conference (CR, 64).

practical
system of
units of
measurement

Proposal for establishing a practical system of units of measurement (CR, 64).

RESOLUTION 6

The General Conference,

considering

that the CIPM has been requested by the International Union of Physics to adopt for international use a practical international system of units; that the International Union of Physics recommends the MKS system and one electric unit of the absolute practical system, but does not recommend that the CGS system be abandoned by physicists;

that the CGPM has itself received from the French Government a similar request, accompanied by a draft to be used as basis of discussion for the establishment of a complete specification of units of measurement;

instructs the CIPM:

to seek by an energetic, active, official enquiry the opinion of scientific, technical, and educational circles of all countries (offering them in effect the French document as basis);

to gather and study the answers;

⁹ A table, prepared in response to this request, was approved and published by the CIPM in 1950 (PV, 22, 92).

to make recommendations for a single practical system of units of measurement, suitable for adoption by all countries adhering to the Meter Convention.

symbols and numbers

Writing and printing of unit symbols and of numbers (CR, 70)

RESOLUTION 7

Principles

Roman (upright) type, in general lower case, is used for symbols of units; if however the symbols are derived from proper names, capital roman type is used. These symbols are not followed by a full stop.

In numbers, the comma (French practice) or the dot (British practice) is used only to separate the integral part of numbers from the decimal part. Numbers may be divided in groups of three in order to facilitate reading; neither dots nor commas are ever inserted in the spaces between groups.

Unit	Symbol	Unit	Symbol
·meter	m	ampere	A
·square meter	m ²	volt	V
·cubic meter	m ³	watt	W
·micron*	μ	ohm	Ω
·liter**	l	coulomb	C
·gram	g	farad	F
·metric ton	t	henry	H
second	s	hertz	Hz
erg	erg	poise	P
dyne	dyn	newton	N
degree Celsius	°C	·candela ("new candle"*)	cd
·degree absolute***	°K	lux	lx
calorie	cal	lumen	lm
bar	bar	stilb	sb
hour	h		

Notes

I. The symbols whose unit names are preceded by dots are those which had already been adopted by a decision of the CIPM.

II. The symbol for the stere, the unit of volume for firewood, shall be "st" and not "s," which had been previously assigned to it by the CIPM.

III. To indicate a temperature interval or difference, rather than temperature, the word "degree" in full, or the abbreviation "deg," must be used.****

* See p. 32, Resolution 7 of the 13th CGPM (1967).

** An alternative symbol, L, was adopted in 1979 (see p. 37: 16th CGPM, Resolution 6).

*** Name and symbol changed in 1967 (see p. 30: 13th CGPM, Resolution 3).

**** Decision abrogated in 1967 (see p. 30: 13th CGPM, Resolution 3).

thermo-
dynamic
scale

Definition of the thermodynamic temperature scale (CR, 79)

RESOLUTION 3

The 10th CGPM decides to define the thermodynamic temperature scale by choosing the triple point of water as the fundamental fixed point, and assigning to it the temperature 273.16 degrees Kelvin, exactly.*

* See p. 31, Resolution 4 of the 13th CGPM, 1967, which explicitly defines the kelvin.

standard
atmosphere

Definition of standard atmosphere (CR, 79)

RESOLUTION 4

The 10th CGPM, having noted that the definition of the standard atmosphere given by the 9th CGPM when defining the International Temperature Scale led some physicists to believe that this definition of the standard atmosphere was valid only for accurate work in thermometry,

declares that it adopts, for general use, the definition:

1 standard atmosphere = 1 013 250 dynes per square centimeter, i.e.,
101 325 newtons per square meter.


practical
system
of units

Practical system of units (CR, 80)

RESOLUTION 6

In accordance with the wish expressed by the 9th CGPM in its Resolution 6 concerning the establishment of a practical system of units of measurement for international use, the 10th CGPM

decides to adopt as base units of the system, the following units:

length	meter
mass	kilogram
time	second
electric current	ampere
thermodynamic temperature	degree Kelvin*
luminous intensity	candela 

*Name changed to "kelvin" in 1967 (see p. 30: 13th CGPM, Resolution 3).

second

Definition of the unit of time (PV, 25, 77)

RESOLUTION 1

In virtue of the powers invested in it by Resolution 5 of the 10th CGPM, the CIPM

considering

1 that the 9th General Assembly of the International Astronomical Union (Dublin, 1955) declared itself in favor of linking the second to the tropical year;

2 that, according to the decisions of the 8th General Assembly of the International Astronomical Union (Rome, 1952), the second of ephemeris time (ET) is the fraction

$$\frac{12\,960\,276\,813}{408\,986\,496} \times 10^{-9} \text{ of the tropical year for 1900 January 0 at 12 h ET,}$$

decides

“The second is the fraction $1/31\,556\,925.974\,7$ of the tropical year for 1900 January 0 at 12 hours ephemeris time.”*

* Definition abrogated in 1967 (see p. 30: 13th CGPM, Resolution 1).

SI

International System of Units (PV, 25, 83)

RESOLUTION 3

The CIPM

considering

the task entrusted to it by Resolution 6 of the 9th CGPM concerning the establishment of a practical system of units of measurement suitable for adoption by all countries adhering to the Meter Convention,

the documents received from twenty-one countries in reply to the enquiry requested by the 9th CGPM,

Resolution 6 of the 10th CGPM, fixing the base units of the system to be established

recommends

1 that the name “International System of Units” be given to the system founded on the base units adopted by the 10th CGPM, viz:

[here follows the list of the six base units with their symbols, reproduced in Resolution 12 of the 11th CGPM (1960)]

2 that the units listed in the table below be used, without excluding others which might be added later:

[here follows the table of units reproduced in paragraph 4 of Resolution 12 of the 11th CGPM (1960)]

meter*Definition of the meter* (CR, 85)

RESOLUTION 6

The 11th CGPM

considering

that the international Prototype does not define the meter with an accuracy adequate for the present needs of metrology,

that it is moreover desirable to adopt a natural and indestructible standard,

decides

1 The meter is the length equal to 1 650 763.73 wavelengths in vacuum of the radiation corresponding to the transition between the levels $2p_{10}$ and $5d_5$ of the krypton 86 atom.

2 The definition of the meter in force since 1889, based on the international Prototype of platinum-iridium, is abrogated.

3 The international Prototype of the meter sanctioned by the 1st CGPM in 1889 shall be kept at the BIPM under the conditions specified in 1889.

RESOLUTION 7

The 11th CGPM

requests the CIPM

1 to prepare specifications for the realization of the new definition of the meter;¹⁰

2 to select secondary wavelength standards for measurement of length by interferometry, and to prepare specifications for their use;

3 to continue the work in progress on improvement of length standards.

second*Definition of the unit of time* (CR, 86)

RESOLUTION 9

The 11th CGPM

considering

the powers given to the CIPM by the 10th CGPM, to define the fundamental unit of time,

the decision taken by the CIPM in 1956,

ratifies the following definition:

“The second is the fraction $1/31\,556\,925.974\,7$ of the tropical year for 1900 January 0 at 12 hours ephemeris time.”*

* Definition abrogated in 1967 (see p. 30: 13th CGPM, Resolution 1).

¹⁰ See Appendix II, p. 39, for the relevant Recommendation adopted by the CIPM.

RESOLUTION 12

The 11th CGPM

considering

Resolution 6 of the 10th CGPM, by which it adopted six base units on which to establish a practical system of measurement for international use:

length	meter	m
mass	kilogram	kg
time	second	s
electric current	ampere	A
thermodynamic temperature	degree Kelvin	°K*
luminous intensity	candela	cd

Resolution 3 adopted by the CIPM in 1956,

the recommendations adopted by the CIPM in 1958 concerning an abbreviation for the name of the system, and prefixes to form multiples and sub-multiples of the units,

decides

- 1 the system founded on the six base units above is called "International System of Units;""**
- 2 the international abbreviation of the name of the system is: SI,
- 3 names of multiples and sub-multiples of the units are formed by means of the following prefixes:***

Multiplying factor	Prefix	Symbol
1 000 000 000 000 = 10^{12}	tera	T
1 000 000 000 = 10^9	giga	G
1 000 000 = 10^6	mega	M
1 000 = 10^3	kilo	k
100 = 10^2	hecto	h
10 = 10^1	deka	da
0.1 = 10^{-1}	deci	d
0.01 = 10^{-2}	centi	c
0.001 = 10^{-3}	milli	m
0.000 001 = 10^{-6}	micro	μ
0.000 000 001 = 10^{-9}	nano	n
0.000 000 000 001 = 10^{-12}	pico	p

- 4 the units listed below are used in the system, without excluding others which might be added later

SUPPLEMENTARY UNITS

plane angle	radian	rad
solid angle	steradian	sr

* Name and symbol of unit modified in 1967 (see p. 30: 13th CGPM, Resolution 3).

** A seventh base unit, the mole, was adopted in 1971 by the 14th CGPM (Resolution 3, see p. 34).

*** See pages 29 and 36 for the four new prefixes adopted by the 12th CGPM (1964), Resolution 8, and the 15th CGPM (1975), Resolution 10.

DERIVED UNITS****

area	square meter	m^2	
volume	cubic meter	m^3	
frequency	hertz	Hz	1/s
mass density (density)	kilogram per cubic meter	kg/m^3	
speed, velocity	meter per second	m/s	
angular velocity	radian per second	rad/s	
acceleration	meter per second squared	m/s^2	
angular acceleration	radian per second squared	rad/s^2	
force	newton	N	$kg \cdot m/s^2$
pressure (mechanical stress)	newton per square meter	N/m^2	
kinematic viscosity	square meter per second	m^2/s	
dynamic viscosity	newton-second per square meter	$N \cdot s/m^2$	
work, energy, quantity of heat	joule	J	N·m
power	watt	W	J/s
quantity of electricity	coulomb	C	A·s
potential difference, electromotive force	volt	V	W/A
electric field strength	volt per meter	V/m	
electric resistance	ohm	Ω	V/A
capacitance	farad	F	A·s/V
magnetic flux	weber	Wb	V·s
inductance	henry	H	V·s/A
magnetic flux density	tesla	T	Wb/m ²
magnetic field strength	ampere per meter	A/m	
magnetomotive force	ampere	A	
luminous flux	lumen	lm	cd·sr
luminance	candela per square meter	cd/m^2	
illuminance	lux	lx	lm/m ²

**** See page 32 for the other units added by the 13th CGPM (1967), Resolution 6.

cubic decimeter and liter

Cubic decimeter and liter (CR, 88)

RESOLUTION 13

The 11th CGPM,

considering

that the cubic decimeter and the liter are unequal and differ by about 28 parts in 10^6 ,

that determinations of physical quantities which involve measurements of volume are being made more and more accurately, thus increasing the risk of confusion between the cubic decimeter and the liter,

requests the CIPM to study the problem and submit its conclusions to the 12th CGPM.

CIPM, 1961

cubic decimeter and liter (PV, 29, 34)

RECOMMENDATION

The CIPM recommends that the results of accurate measurements of volume be expressed in units of the International System and not in liters.

12th CGPM, 1964

frequency standard

Atomic standard of frequency (CR, 93)

RESOLUTION 5

The 12th CGPM,

considering

that the 11th CGPM noted in its Resolution 10 the urgency, in the interests of accurate metrology, of adopting an atomic or molecular standard of time interval,

that, in spite of the results already obtained with cesium atomic frequency standards, the time has not yet come for the CGPM to adopt a new definition of the second, base unit of the International System of Units, because of the new and considerable improvements likely to be obtained from work now in progress,

considering also that it is not desirable to wait any longer before time measurements in physics are based on atomic or molecular frequency standards,

empowers the CIPM to name the atomic or molecular frequency standards to be employed for the time being,

requests the Organizations and Laboratories knowledgeable in this field to pursue work connected with a new definition of the second.

DECLARATION OF THE CIPM (1964) (PV, 32, 26, and CR, 93)

The CIPM,

empowered by Resolution 5 of the 12th CGPM to name atomic or molecular frequency standards for temporary use for time measurements in physics,

declares that the standard to be employed is the transition between the hyperfine levels $F=4, M=0$ and $F=3, M=0$ of the ground state $^2S_{1/2}$ of the cesium 133 atom, unperturbed by external fields, and that the frequency of this transition is assigned the value 9 192 631 770 hertz.

RESOLUTION 6

The 12th CGPM,

considering Resolution 13 adopted by the 11th CGPM in 1960 and the Recommendation adopted by the CIPM in 1961,

- 1 *abrogates* the definition of the liter given in 1901 by the 3d CGPM
- 2 *declares* that the word “liter” may be employed as a special name for the cubic decimeter.
- 3 *recommends* that the name liter should not be employed to give the results of high accuracy volume measurements.

RESOLUTION 7

The 12th CGPM,

considering that the curie has been used for a long time in many countries as a unit of activity for radionuclides,

recognizing that in the International System of Units (SI), the unit of this activity is the second to the power of minus one (s^{-1}),*

accepts that the curie be still retained outside SI as unit of activity, with the value $3.7 \times 10^{10} s^{-1}$. The symbol for this unit is Ci.

* In 1975 the name “becquerel” (Bq) was adopted for the SI unit of activity (see p. 35: 15th CGPM, Resolution 8); $1 \text{ Ci} = 3.7 \times 10^{10} \text{ Bq}$.

RESOLUTION 8

The 12th CGPM,

decides to add to the list of prefixes for the formation of names of multiples and sub-multiples of units, adopted by the 11th CGPM, Resolution 12, paragraph 3, the following two new prefixes:

Multiplying factor	Prefix	Symbol
10^{-15}	femto	f
10^{-18}	atto	a

second

SI unit of time (second) (CR, 103)

RESOLUTION 1

The 13th CGPM,

considering

that the definition of the second adopted by the CIPM in 1956 (Resolution 1) and ratified by Resolution 9 of the 11th CGPM (1960), later upheld by Resolution 5 of the 12th CGPM (1964), is inadequate for the present needs of metrology,

that at its meeting of 1964 the CIPM, empowered by Resolution 5 of the 12th CGPM (1964), recommended, in order to fulfill these requirements, a cesium atomic frequency standard for temporary use,

that this frequency standard has now been sufficiently tested and found sufficiently accurate to provide a definition of the second fulfilling present requirements,

that the time has now come to replace the definition now in force of the unit of time of the International System of Units by an atomic definition based on that standard,

decides

1 The SI unit of time is the second defined as follows:

“The second is the duration of 9 192 631 770 periods of the radiation corresponding to the transition between the two hyperfine levels of the ground state of the cesium 133 atom.”

2 Resolution 1 adopted by the CIPM at its meeting of 1956 and Resolution 9 of the 11th CGPM are now abrogated.

kelvin
(degree
Celsius)*SI unit of thermodynamic temperature (kelvin) (CR, 104)*

RESOLUTION 3

The 13th CGPM

considering

the names “degree Kelvin” and “degree,” the symbols “°K” and “deg,” and the rules for their use given in Resolution 7 of the 9th CGPM (1948), in Resolution 12 of the 11th CGPM (1960), and the decision taken by the CIPM in 1962 (PV, 30, 27), that the unit of thermodynamic temperature and the unit of temperature interval are one and the same unit, which ought to be denoted by a single name and single symbol,

decides

1 the unit of thermodynamic temperature is denoted by the name “kelvin” and its symbol is “K”;

2 the same name and the same symbol are used to express a temperature interval;

3 a temperature interval may also be expressed in degrees Celsius;

4 the decisions mentioned in the opening paragraph concerning the name of the unit of thermodynamic temperature, its symbol, and the designation of the unit to express an interval or a difference of temperatures are abrogated, but the usages which derive from these decisions remain permissible for the time being.*

*At its 1980 meeting the CIPM approved the report of the 7th meeting of the CCU which requested that the use of the symbols “°K” and “deg” no longer be permitted.

RESOLUTION 4

The 13th CGPM,

kelvin

considering that it is useful to formulate more explicitly the definition of the unit of thermodynamic temperature contained in Resolution 3 of the 10th CGPM (1954).

decides to express this definition as follows:

“The kelvin, unit of thermodynamic temperature, is the fraction $1/273.16$ of the thermodynamic temperature of the triple point of water.”

candela

SI unit of luminous intensity (candela) (CR, 104)

RESOLUTION 5

The 13th CGPM

considering

the definition of the unit of luminous intensity ratified by the 9th CGPM (1948) and contained in the “Resolution concerning the change of photometric units” adopted by CIPM in 1946 (PV, 20, 119) in virtue of the powers conferred by the 8th CGPM (1933),

that this definition fixes satisfactorily the unit of luminous intensity, but that its wording may be open to criticism,

decides to express the definition of the candela as follows:

“The candela is the luminous intensity, in the perpendicular direction, of a surface of $1/600\,000$ square meter of a blackbody at the temperature of freezing platinum under a pressure of $101\,325$ newtons per square meter.”*

* Definition abrogated in 1979 (see p. 36: 16th CGPM, Resolution 3).

RESOLUTION 6

The 13th CGPM

considering that it is useful to add some derived units to the list of paragraph 4 of Resolution 12 of the 11th CGPM (1960),

decides to add:

wave number	1 per meter	m^{-1}
entropy	joule per kelvin	J/K
specific heat capacity	joule per kilogram kelvin	$\text{J}/(\text{kg}\cdot\text{K})$
thermal conductivity	watt per meter kelvin	$\text{W}/(\text{m}\cdot\text{K})$
radiant intensity	watt per steradian	W/sr
activity (of a radioactive source)	1 per second	s^{-1} *

* The unit of activity received a special name and symbol in 1975 (see p. 35: 15th CGPM, Resolution 8).

micron (μ)
new candle

Abrogation of earlier decisions (micron, new candle) (CR, 105)

RESOLUTION 7

The 13th CGPM,

considering that subsequent decisions of the General Conference concerning the International System of Units are incompatible with parts of Resolution 7 of the 9th CGPM (1948),

decides accordingly to remove from Resolution 7 of the 9th Conference:

- 1 the unit name "micron", and the symbol " μ " which had been given to that unit, but which has now become a prefix;
- 2 the unit name "new candle."

CIPM, 1967

multiples of
kilogram

Decimal multiples and sub-multiples of the unit of mass (PV, 35, 29)

RECOMMENDATION 2

The CIPM,

considering that the rule for forming names of decimal multiples and sub-multiples of the units of paragraph 3 of Resolution 12 of the 11th CGPM (1960) might be interpreted in different ways when applied to the unit of mass,

declares that the rules of Resolution 12 of the 11th CGPM apply to the kilogram in the following manner: the names of decimal multiples and sub-multiples of the unit of mass are formed by attaching prefixes to the word "gram."

CIPM, 1969

SI

International System of Units: Rules for application of Resolution 12 of the 11th CGPM (1960) (PV, 37, 30)

RECOMMENDATION 1 (1969)

The CIPM,

considering that Resolution 12 of the 11th CGPM (1960) concerning the International System of Units, has provoked discussions on certain of its aspects,

declares

1 the base units, the supplementary units, and the derived units, of the International System of Units, which form a coherent set, are denoted by the name “SI units”;

2 the prefixes adopted by the CGPM for the formation of decimal multiples and sub-multiples of SI units are called “SI prefixes”;

and *recommends*

3 the use of SI units, and of their decimal multiples and sub-multiples whose names are formed by means of SI prefixes.

Note: The name “supplementary units,” appearing in Resolution 12 of the 11th CGPM (and in the present Recommendation) is given to SI units for which the General Conference declines to state whether they are base units or derived units.*

* See p. 38: Recommendation 1 (CI-1980) of the CIPM.

14th CGPM, 1971

pascal;
siemens

Pascal; siemens

The 14th CGPM (CR, p. 59) adopted the special names “pascal” (symbol Pa), for the SI unit newton per square meter, and “siemens” (symbol S), for the SI unit of electric conductance (reciprocal ohm).

TAI

International Atomic Time; function of CIPM (CR, 77)

RESOLUTION 1

The 14th CGPM

considering

that the second, unit of time of the International System of Units, has since 1967 been defined in terms of a natural atomic frequency, and no longer in terms of the time scales provided by astronomical motions,

that the need for an International Atomic Time (TAI) scale is a consequence of the atomic definition of the second,

that several international organizations have ensured and are still successfully ensuring the establishment of time scales based on astronomical motions, particularly thanks to the permanent services of the Bureau International de l'Heure (BIH),

that BIH has started to establish an atomic time scale of recognized quality and proven usefulness,

that the atomic frequency standards for realizing the second have been considered and must continue to be considered by CIPM, helped by a Consultative Committee, and that the unit interval of the International Atomic Time scale must be the second realized according to its atomic definition,

that all the competent international scientific organizations and the national laboratories active in this field have expressed the wish that CIPM and CGPM should give a definition of International Atomic Time, and should contribute to the establishment of the International Atomic Time scale,

that the usefulness of International Atomic Time entails close coordination with the time scales based on astronomical motions,

requests CIPM

1 to give a definition of International Atomic Time;¹¹

2 to take the necessary steps, in agreement with the international organizations concerned, to ensure that available scientific competence and existing facilities are used in the best possible way to realize the International Atomic Time scale and to satisfy the requirements of users of International Atomic Time.

mole

SI unit of amount of substance (mole) (CR, 78)

RESOLUTION 3

The 14th CGPM

considering the advice of the International Union of Pure and Applied Physics, of the International Union of Pure and Applied Chemistry, and of the International

¹¹ In anticipation of this request, CIPM had asked the Consultative Committee for the Definition of the Second (CCDS), to prepare a definition of International Atomic Time. This definition, approved by CIPM at its 59th session (October 1970), is as follows:

"International Atomic Time [TAI] is the time reference coordinate established by the Bureau International de l'Heure on the basis of the readings of atomic clocks operating in various establishments in accordance with the definition of the second, the unit of time of the International System of Units."

Organization for Standardization, concerning the need to define a unit of amount of substance,

decides

1 The mole is the amount of substance of a system that contains as many elementary entities as there are atoms in 0.012 kilogram of carbon 12*; its symbol is “mol.”

2 When the mole is used, the elementary entities must be specified and may be atoms, molecules, ions, electrons, other particles, or specified groups of such particles.

3 The mole is a base unit of the International System of Units.

* At its 1980 meeting, the CIPM approved the report of the 7th meeting of the CCU specifying that “in this definition, it is understood that unbound atoms of carbon 12, at rest and in their ground state, are referred to.”

15th CGPM, 1975

UTC

Universal Coordinated Time (CR, 104)

RESOLUTION 5

The 15th CGPM

considering that the system called “Coordinated Universal Time” (UTC) is widely used, that it is broadcast in most radio transmissions of time signals, that this wide diffusion makes available to the users not only frequency standards but also International Atomic Time and an approximation to Universal Time (or, if one prefers, mean solar time),

notes that Coordinated Universal Time provides the basis of civil time, the use of which is legal in most countries,

judgets that this usage can be strongly endorsed.

becquerel
gray

SI units for ionizing radiation (CR, 105)

RESOLUTIONS 8 and 9

The 15th CGPM

—by reason of the pressing requirement, expressed by the International Commission on Radiation Units and Measurements (ICRU), to extend the use of the International System of Units to radiological research and applications,

—by reason of the need to make as easy as possible the use of the units for non-specialists,

—taking into consideration also the grave risk of errors in therapeutic work,

adopts the following special name for the SI unit of activity:

becquerel, symbol Bq, equal to one reciprocal second.

} RESOLUTION 8

adopts the following special name for an SI unit in the field of ionizing radiation: gray, symbol Gy, equal to one joule per kilogram. } **RESOLUTION 9**

Note: The gray is the SI unit of absorbed dose. In the field of ionizing radiation the gray may also be used with other physical quantities also expressed in joules per kilogram; the Consultative Committee for Units is made responsible for studying this matter in collaboration with the competent international organizations.[†]

[†] Translators' note: It has since been agreed (CCU, 1976; CIPM, 1977) that the gray may be used to express the four quantities absorbed dose, specific energy imparted, kerma, and absorbed dose index.

peta
exa

SI prefixes peta and exa (CR, 106)

RESOLUTION 10

The 15th CGPM

decides to add to the list of SI prefixes to be used for multiples, which was adopted by the 11th CGPM, Resolution 12, paragraph 3, the two following prefixes:

Multiplying factor	Prefix	Symbol
10^{15}	peta	P
10^{18}	exa	E

16th CGPM, 1979

candela

SI unit of luminous intensity (candela) (CR, 100)

RESOLUTION 3

The 16th CGPM

considering

that despite the notable efforts of some laboratories there remain excessive divergences between the results of realizations of the candela based upon the present blackbody primary standard,

that radiometric techniques are developing rapidly, allowing precisions that are already equivalent to those of photometry and that these techniques are already in use in national laboratories to realize the candela without having to construct a blackbody,

that the relation between luminous quantities of photometry and radiometric quantities, namely the value of 683 lumens per watt for the spectral luminous efficacy of monochromatic radiation of frequency 540×10^{12} hertz, has been adopted by the International Committee for Weights and Measures in 1977,

that this value has been accepted as being sufficiently accurate for the system of luminous photopic quantities, that it implies a change of only about 3% for the system of luminous scotopic quantities, and that it therefore ensures satisfactory continuity,

that the time has come to give the candela a definition that will allow an improvement in both the ease of realization and precision of photometric standards, and that applies to both photopic and scotopic photometric quantities and to quantities yet to be defined in the mesopic field,

decides

1 The candela is the luminous intensity, in a given direction, of a source that emits monochromatic radiation of frequency 540×10^{12} hertz and that has a radiant intensity in that direction of (1/683) watt per steradian.

2 The definition of the candela (at the time called new candle) adopted by the CIPM in 1946 by reason of the powers conferred by the 8th CGPM in 1933, ratified by the 9th CGPM in 1948, then amended by the 13th CGPM in 1967, is abrogated.

sievert

Special name for the SI unit of dose equivalent (CR, 100)

RESOLUTION 5

The 16th CGPM

considering

the effort made to introduce SI units into the field of ionizing radiations,

the risk to human beings of an underestimated radiation dose, a risk that could result from a confusion between absorbed dose and dose equivalent,

that the proliferation of special names represents a danger for the International System of Units and must be avoided in every possible way, but that this rule can be broken when it is a matter of safeguarding human health,

adopts the special name *sievert*, symbol Sv, for the SI unit of dose equivalent in the field of radioprotection. The sievert is equal to the joule per kilogram.[†]

[†] Translators' note: It should be noted that the quantity dose equivalent, H , is the product of the absorbed dose, D , of ionizing radiation, and the dimensionless factors Q (quality factor) and N (product of any other multiplying factors) stipulated by the International Commission on Radiological Protection. Thus, for a given irradiation, the numerical value in joules per kilogram of these two quantities D and H may differ, depending on the values of Q and N . To avoid any risk of confusion, the special names for the respective *units* should be used; i.e., D should be expressed in grays, and H should be expressed in sieverts.

liter

Symbols for the liter (CR, 101)

RESOLUTION 6

The 16th CGPM

recognizing the general principles adopted for writing the unit symbols in Resolution 7 of the 9th CGPM (1948),

considering that the symbol l for the unit liter was adopted by the CIPM in 1879 and confirmed in the same Resolution of 1948,

considering also that, in order to avoid the risk of confusion between the letter l and the number 1, several countries have adopted the symbol L instead of l for the unit liter,

considering that the name liter, although not included in the International System of Units, must be admitted for general use with the System,

decides, as an exception, to adopt the two symbols l and L as symbols to be used for the unit liter,

considering further that in the future only one of these two symbols should be retained,

invites the CIPM to follow the development of the use of these two symbols and to give the 18th CGPM its opinion as to the possibility of suppressing one of them.

CIPM, 1980

SI supplementary units

SI supplementary units (radian and steradian) (PV, 48)

RECOMMENDATION 1 (CI-1980)

The CIPM,

taking into consideration Resolution 3 adopted by ISO/TC12 in 1978 and Recommendation U1 (1980) adopted by the Consultative Committee for Units (CCU) at its 7th meeting,

considering that the units radian and steradian are usually introduced into expressions for units when there is need for clarification, especially in photometry where the steradian plays an important role in distinguishing between units corresponding to different quantities,

that in the equations used one generally expresses plane angle as the ratio of two lengths and solid angle as the ratio between an area and the square of a length, and consequently that these quantities are treated as dimensionless quantities,

that the study of the formalisms in use in the scientific field shows that none exists which is at the same time coherent and convenient and in which the quantities plane angle and solid angle might be considered as base quantities,

considering also

that the interpretation given by the CIPM in 1969 for the class of supplementary units introduced in Resolution 12 of the 11th CGPM in 1960 allows the freedom of treating the radian and the steradian as SI base units,

that such a possibility compromises the internal coherence of the SI based on only seven base units,

decides to interpret the class of supplementary units in the International System as a class of dimensionless derived units for which the CGPM allows the freedom of using or not using them in expressions for SI derived units.

APPENDIX II

Practical realization of the definitions of some important units

1. Length

The following recommendation was adopted by the CIPM in 1960 to specify the characteristics of the discharge lamp radiating the standard line of krypton 86:

In accordance with paragraph 1 of Resolution 7 adopted by the 11th CGPM (October 1960) the CIPM recommends that the line of krypton 86 adopted as primary standard of length be realized by means of a hot cathode discharge lamp containing krypton 86 of purity not less than 99% in sufficient quantity to ensure the presence of solid krypton at a temperature of 64 °K. The lamp shall have a capillary of internal diameter 2 to 4 millimeters, and wall thickness approximately 1 millimeter.

It is considered that, provided the conditions listed below are satisfied, the wavelength of the radiation emitted by the positive column is equal to the wavelength corresponding to the transition between the unperturbed levels to within 1 in 10^8 :

1. the capillary is observed end-on in a direction such that the light rays used travel from the cathode end to the anode end;
 2. the lower part of the lamp including the capillary is immersed in a bath maintained to within 1 degree of the temperature of the triple point of nitrogen;
 3. the current density in the capillary is 0.3 ± 0.1 ampere per square centimeter.
- (*Procès-Verbaux CIPM*, 28, 1960, 71; *Comptes rendus 11th CGPM*, 1960, 85)

The ancillary apparatus comprises the stabilized current supply for the lamp, a vacuum-tight cryostat, a thermometer for use in the region of 63 K, a vacuum pump, and either a monochromator, to isolate the line, or special interference filters.

Other lines of krypton 86 and several lines of mercury 198 and of cadmium 114 are recommended as secondary standards (*Procès-Verbaux CIPM*, 31, 1963, Recommendation 1, 26 and *Comptes rendus 12th CGPM*, 1964, 18).

Two monochromatic radiations, one in the visible the other in the infrared spectral region, produced by helium-neon lasers stabilized on a saturated absorption line of iodine or of methane, are recommended as wavelength standards with the following values (PV CIPM, 41, 1973, 112)

Line	Wavelength in vacuum
Methane, P(7), band ν_3	$3\,392\,231.40 \times 10^{-12}$ m
Iodine 127, R(127), band 11-5 component i	$632\,991.399 \times 10^{-12}$ m

These lines are reproducible with an uncertainty of the order of 1 in 10^{10} ; the value of their wavelength in meters is subject to the uncertainty of the standard (the wavelength of the ^{86}Kr line) estimated to be 4 in 10^9 . By measuring the beat frequencies of neighboring lines (for example various components of the hyperfine multiplet of iodine), very exact values of the wavelength differences are obtained.

The wavelengths of all these lines vary with pressure, temperature, and composition of the air in which the light travels; the refractive index of the air must therefore in general be measured *in situ*.

To measure end or line standards these radiations are used in an interference comparator, a complicated instrument with mechanical, optical interference, and thermometric components.

The wavelength of the methane line mentioned above multiplied by its frequency (measured by comparison with the ^{133}Cs transition of the definition of the second) yields the speed of propagation of electromagnetic waves in vacuum $c=299\,792\,458\text{ m/s}$, recommended by the 15th CGPM (Resolution 2).

2. Mass

The primary standard of the unit of mass is the international prototype of the kilogram kept at the BIPM. The mass of 1-kg secondary standards of platinum-iridium or of stainless steel is compared with the mass of the prototype by means of balances whose precision can reach 1 in 10^8 or better. In the case of stainless steel standards, the accuracy of the comparison depends upon the accuracy with which the correction due to air buoyancy is known.

By an easy operation a series of masses can be standardized to obtain multiples and sub-multiples of the kilogram.

3. Time

Some research laboratories are able to construct the equipment required to produce electric oscillations at a frequency whose relationship to the transition frequency of the atom of cesium 133 which defines the second is known. It is possible thus to obtain pulses at desired frequencies, 1 Hz, 1 kHz, etc. Some cesium time standards are also commercially available.

In the best equipment, the accuracy corresponds to an uncertainty of a part in 10^{13} or even in 10^{14} .

Radio stations broadcast waves whose frequencies are known with an uncertainty of a part in 10^{11} or 10^{12} .

There exist very stable clocks and frequency generators besides those using cesium, including the hydrogen maser, and rubidium and quartz clocks. Their frequency has to be standardized by comparison with a cesium time standard, either directly, or by means of radio transmissions.

Time signals broadcast by radio waves are given in a time scale called Coordinated Universal Time (UTC) as recommended by the 15th CGPM (Resolution 5) in 1975. UTC is defined in such a manner that it differs from TAI¹² by a whole number of seconds. The difference UTC-TAI was set equal to -10 s starting the first of January 1972, the date of application of the reformulation of UTC which previously involved a frequency offset; this difference can be modified by 1 second, by the use of a positive or negative leap second at the end of a month of UTC, preferably in the first instance at the end of December or of June, and in the second instance at the end of March or of September, to keep UTC in agreement with the time defined by the rotation of Earth with an approximation better than 0.9 s .¹³ Furthermore, the legal times of most countries are offset by a whole number of hours (time zones and "daylight saving" time).

¹² See Appendix I, page 34 (footnote 11), for the definition of TAI given by CIPM at the request of the 14th CGPM (1971, Resolution 1).

¹³ The difference UTC-TAI was -19 s on 1 Jan. 1981.

4. Electric quantities

So-called "absolute" electrical measurements, i.e., those that realize the unit according to its definition, can be undertaken only by laboratories enjoying exceptional facilities.

Electric current is obtained in amperes by measuring the force between two coils, of measurable shape and size, that carry the current.

The ohm, the farad, and the henry are accurately linked by impedance measurements at a known frequency, and may be determined in absolute value by calculation (1) of the self-inductance of a coil, or the mutual inductance of two coils, in terms of their linear dimensions, or (2) of the change in capacitance of a capacitor in terms of the change in length of its electrodes (method of Thompson-Lampard).

The volt is deduced from the ampere and the ohm.

The uncertainty in the absolute determination of the farad is a few parts in 10^8 ; for the ampere, it is a few parts in 10^6 .

The results of absolute measurements are obtained by means of secondary standards which are, for instance:

1. coils of manganin wire for resistance standards;
2. galvanic cells with cadmium sulphate electrolyte for standards of electromotive force;
3. capacitors (standards of capacitance of 10 pF for example).

Application of recent techniques also provides means of checking the stability of the secondary standards that maintain the electric units: measurement of the gyromagnetic ratio of the proton γ'_p for the ampere, measurement of the ratio h/e by the Josephson effect for the volt.

5. Temperature

Absolute measurements of temperature in accordance with the definition of the unit of thermodynamic temperature, the kelvin, are related to thermodynamics, for example by the gas thermometer.

At 273.16 K accuracy is of the order of 1 in 10^6 , but it is not as good at higher and at lower temperatures.

The International Practical Temperature Scale of 1968, amended edition of 1975 adopted by the 15th CGPM, agrees with the best thermodynamic results to date. The text on this scale is published in *Comité Consultatif de Thermométrie*, 10th session, 1974, Annexe T31, and *Comptes Rendus*, 15th CGPM, 1975, Annexe 2; the English translation is published in *Metrologia*, 12, No. 1, 7, 1976.

The instruments employed to measure temperatures in the International Scale are the platinum resistance thermometer, the platinum-10% rhodium/platinum thermocouple and the monochromatic optical pyrometer. These instruments are calibrated at a number of reproducible temperatures, called "defining fixed points," the values of which are assigned by agreement.

In 1978, a low temperature scale was established under the name "1976 Provisional Temperature Scale between 0.5 K and 30 K" (EPT-76). This provisional practical scale was published in *Comité Consultatif de Thermométrie*, 12th

session, 1978, p. T 7 and *Procès-Verbaux CIPM*, 46, 1978, p. T 7; the English translation was published in *Metrologia*, 15, 1979, p. 65.

6. Amount of substance

All quantitative results of chemical analysis or of dosages can be expressed in moles, in other words in units of amount of substance of the elementary entities. The principle of physical measurements based on the definition of this unit is explained below.

The simplest case is that of a sample of a pure substance that is considered to be formed of atoms; call X the chemical symbol of these atoms. A mole of atoms X contains by definition as many atoms as there are ^{12}C atoms in 0.012 kilogram of carbon 12. As neither the mass $m(^{12}\text{C})$ of an atom of carbon 12 nor the mass $m(\text{X})$ of an atom X can be measured accurately, we use the ratio of these masses, $m(\text{X})/m(^{12}\text{C})$, which can be accurately determined.¹⁴ The mass corresponding to 1 mole of X is then $[m(\text{X})/m(^{12}\text{C})] \times 0.012$ kg, which is expressed by saying that the molar mass $M(\text{X})$ of X (quotient of mass by amount of substance) is

$$M(\text{X}) = [m(\text{X})/m(^{12}\text{C})] \times 0.012 \text{ kg/mol.}$$

For example, the atom of fluorine ^{19}F and the atom of carbon ^{12}C have masses that are in the ratio 18.9984/12. The molar mass of the molecular gas F_2 is

$$M(\text{F}_2) = \frac{2 \times 18.9984}{12} \times 0.012 \text{ kg/mol} = 0.037\,996\,8 \text{ kg/mol.}$$

The amount of substance corresponding to a given mass of gas F_2 , 0.05 kg for example, is:

$$\frac{0.05 \text{ kg}}{0.037\,996\,8 \text{ kg}\cdot\text{mol}^{-1}} = 1.315\,90 \text{ mol.}$$

In the case of a pure substance that is supposed made up of molecules B, which are combinations of atoms X, Y, ... according to the chemical formula $\text{B} = \text{X}_\alpha \text{Y}_\beta$..., the mass of one molecule is $m(\text{B}) = \alpha m(\text{X}) + \beta m(\text{Y}) + \dots$

This mass is not known with accuracy, but the ratio $m(\text{B})/m(^{12}\text{C})$ can be determined accurately. The molar mass of a molecular substance B is then

$$M(\text{B}) = \frac{m(\text{B})}{m(^{12}\text{C})} \times 0.012 \text{ kg/mol} = \left(\alpha \frac{m(\text{X})}{m(^{12}\text{C})} + \beta \frac{m(\text{Y})}{m(^{12}\text{C})} + \dots \right) \times 0.012 \text{ kg/mol.}$$

The same procedure is used in the more general case when the composition of the substance B is specified as $\text{X}_\alpha \text{Y}_\beta \dots$ even if α, β, \dots are not integers. If we denote the mass ratios $m(\text{X})/m(^{12}\text{C})$, $m(\text{Y})/m(^{12}\text{C})$, ... by $r(\text{X})$, $r(\text{Y})$, ..., the molar mass of the substance B is given by the formula:

$$M(\text{B}) = [\alpha r(\text{X}) + \beta r(\text{Y}) + \dots] \times 0.012 \text{ kg/mol.}$$

There are other methods based on the laws of physics and physical chemistry for measuring amounts of substance; three examples are given below.

¹⁴ There are many methods of measuring this ratio, the most direct one being by the mass spectrograph.

With perfect gases, 1 mole of particles of any gas occupies the same volume at a temperature T and a pressure p (approximately $0.022\,4\text{ m}^3$ at $T=273.15\text{ K}$ and $p=101\,325\text{ Pa}$); hence a method of measuring the ratio of amounts of substance for any two gases (the corrections to apply if the gases are not perfect are well known).

For quantitative electrolytic reactions the ratio of amounts of substance can be obtained by measuring quantities of electricity. For example, 1 mole of Ag and $1/2$ mole of Cu are deposited on a cathode by the same quantity of electricity (approximately $96\,487\text{ C}$).

Application of the laws of Raoult is yet another method of determining ratios of amounts of substance in extremely dilute solutions.

7. Photometric quantities

The method approved by CIPM in 1937 (*Procès-Verbaux CIPM*, **18**, 237) for determining the value of photometric quantities for luminous sources whose radiation does not have the same spectral composition, utilizes a procedure taking account of the “spectral luminous efficiencies” $V(\lambda)$. By its Recommendation 1 (CI-1972), CIPM recommends the use of the $V(\lambda)$ values adopted by the International Commission on Illumination (CIE) in 1971.¹⁵ The weighting function $V(\lambda)$ was obtained for photopic vision, i.e., for retinas adapted to light. For retinas adapted to darkness, another function $V'(\lambda)$ gives the spectral luminous efficiency for scotopic vision (CIE 1951); this function $V'(\lambda)$ was ratified by the CIPM in September 1976.

Photometric quantities are thereby defined in purely physical terms as quantities proportional to the sum or integral of a spectral power distribution, weighted according to a specified function of wavelength.

Before 1979, the standard lamps then in use were calibrated by comparison with the luminance of a Planckian radiator (a blackbody) at the temperature of freezing platinum. Since the adoption of the new definition of the candela in 1979, this measurement is carried out by comparison with the monochromatic radiation specified in the definition, or with some other radiation by taking account of $V(\lambda)$ or $V'(\lambda)$.

The standard lamps are incandescent lamps powered by a specified direct current; they provide either a known luminous flux or, in a given direction, a known luminous intensity.

¹⁵ CIE Publications No. 18 (1970), page 43, and No. 15 (1971), page 93; *Procès-Verbaux CIPM*, **40**, 1972, Annexe 1. The $V(\lambda)$ [$=\bar{v}(\lambda)$] values are given for wavelengths in 1-nm steps from 360 to 830 nm; they are an improvement on the values in 10-nm steps adopted by CIPM in 1933, and previously by CIE in 1924.

APPENDIX III

Organs of the Meter Convention BIPM, CIPM, CGPM

The International Bureau of Weights and Measures (BIPM) was set up by the *Meter Convention* signed in Paris on 20 May 1875 by seventeen States during the final session of the Diplomatic Conference of the Meter. This Convention was amended in 1921.

BIPM has its headquarters near Paris, in the grounds 43 520 m²) of the Pavillon de Breteuil (Parc de Saint-Cloud), placed at its disposal by the French Government; its upkeep is financed jointly by the Member States of the Meter Convention.*

The task of BIPM is to ensure worldwide unification of physical measurements; it is responsible for:

- establishing the fundamental standards and scales for measurement of the principal physical quantities and maintaining the international prototypes;
- carrying out comparisons of national and international standards;
- ensuring the co-ordination of corresponding measuring techniques;
- carrying out and co-ordinating determinations relating to the fundamental physical constants that are involved in the above mentioned activities.

BIPM operates under the exclusive supervision of the *International Committee for Weights and Measures (CIPM)*, which itself comes under the authority of the *General Conference on Weights and Measures (CGPM)*.

The General Conference consists of delegates from all the Member States of the Meter Convention and meets at present every four years. At each meeting it receives the Report of the International Committee on the work accomplished, and it is responsible for:

- discussing and instigating the arrangements required to ensure the propagation and improvement of the International System of Units (SI), which is the modern form of the metric system;
- confirming the results of new fundamental metrological determinations and the various scientific resolutions of international scope;
- adopting the important decisions concerning the organization and development of BIPM.

The International Committee consists of eighteen members each belonging to a different State; it meets at present every year. The officers of this Committee issue an *Annual Report* on the administrative and financial position of BIPM to the Governments of the Member States of the Meter Convention.

* As of 31 December 1980 forty-five States were members of this Convention: Argentina (Rep. of), Australia, Austria, Belgium, Brazil, Bulgaria, Cameroon, Canada, Chile, China (People's Rep. of), Czechoslovakia, Denmark, Dominican Republic, Egypt, Finland, France, German Democratic Rep., Germany (Federal Rep. of), Hungary, India, Indonesia, Iran, Ireland, Italy, Japan, Korea (Rep. of), Mexico, Netherlands, Norway, Pakistan, Poland, Portugal, Romania, Spain, South Africa, Sweden, Switzerland, Thailand, Turkey, U.S.S.R., United Kingdom, U.S.A., Uruguay, Venezuela, Yugoslavia.

The activities of BIPM, which in the beginning were limited to the measurements of length and mass and to metrological studies in relation to these quantities, have been extended to standards of measurement for electricity (1927), photometry (1937), and ionizing radiations (1960). To this end the original laboratories, built in 1876-1878, were enlarged in 1929 and two new buildings were constructed in 1963-1964 for the ionizing radiation laboratories. Some thirty physicists or technicians work in the laboratories of BIPM. They do metrological research, and also undertake measurement and certification of material standards of the above-mentioned quantities. BIPM's annual appropriation is of the order of 8 600 000 gold francs, approximately 3 400 000 U.S. dollars (in 1981).

In view of the extension of the work entrusted to BIPM, CIPM has set up since 1927, under the name of *Consultative Committees*, bodies designed to provide it with information on matters that it refers to them for study and advice. These Consultative Committees, which may form temporary or permanent "Working Groups" to study special subjects, are responsible for co-ordinating the international work carried out in their respective fields and proposing recommendations concerning the amendments to be made to the definitions and values of units. In order to ensure worldwide uniformity in units of measurement, the International Committee accordingly acts directly or submits proposals for sanction by the General Conference.

The Consultative Committees have common regulations (*Procès-Verbaux CIPM*, 1963, 31, 97). Each Consultative Committee, the chairman of which is normally a member of CIPM, is composed of delegates from the major Metrology Laboratories and specialized Institutes, a list of which is drawn up by CIPM, as well as individual members also appointed by CIPM and one representative of BIPM. These Committees hold their meetings at irregular intervals; at present there are eight of them in existence.

1. *The Consultative Committee for Electricity* (CCE), set up in 1927.
2. *The Consultative Committee for Photometry and Radiometry* (CCPR), new name given in 1971 to the Consultative Committee for Photometry set up in 1933 (between 1930 and 1933 the preceding Committee (CCE) dealt with matters concerning Photometry).
3. *The Consultative Committee for Thermometry* (CCT), set up in 1937.
4. *The Consultative Committee for the Definition of the Meter* (CCDM), set up in 1952.
5. *The Consultative Committee for the Definition of the Second* (CCDS), set up in 1956.
6. *The Consultative Committee for the Standards of Measurement of Ionizing Radiations* (CCEMRI), set up in 1958.

In 1969 this Consultative Committee established four sections: Section I (Measurement of x and γ rays, electrons); Section II (Measurement of radio-nuclides); Section III (Neutron measurements); Section IV (α -energy standards). In 1975 this last section was dissolved and Section II made responsible for its field of activity.

7. *The Consultative Committee for Units* (CCU), set up in 1964 (this Consultative Committee replaced the "Commission for the System of Units" set up by the CIPM in 1954).
8. *The Consultative Committee for Mass and Related Quantities* (CCM), set up in 1980.

The proceedings of the General Conference, the International Committee, the Consultative Committees, and the International Bureau are published under the auspices of the latter in the following series:

- Comptes rendus des séances de la Conférence Générale des Poids et Mesures*;
- Procès-Verbaux des séances du Comité International des Poids et Mesures*
- Sessions des Comités Consultatifs*;
- Recueil de Travaux du Bureau International des Poids et Mesures* (this collection for private distribution brings together articles published in scientific and technical journals and books, as well as certain work published in the form of duplicated reports).

From time to time BIPM publishes a report on the development of the Metric System throughout the world, entitled *Les récents progrès du Système Métrique*.

The collection of the *Travaux et Mémoires du Bureau International des Poids et Mesures* (22 volumes published between 1881 and 1966) ceased in 1966 by a decision of CIPM.

Since 1965 the international journal *Metrologia*, edited under the auspices of CIPM, has published articles on the more important work on scientific metrology carried out throughout the world, on the improvement in measuring methods and standards, on units, etc., as well as reports concerning the activities, decisions, and recommendations of the various bodies created under the Meter Convention.

Index

(Numbers in boldface indicate the pages where the definitions of the units are to be found)

	Page		Page
acceleration due to gravity, standard value of (g_n)	18	joule	19
amount of substance	42		
ampere	4, 20, 41		
atmosphere, standard	23		
atto	29	kelvin	4, 30, 31
		kilogram	3, 12, 17
		kilogram, multiples of	32
becquerel	35		
Bureau, International, of Weights and Measures (BIPM)	44-46	legislation on units	2
		length	39
		liter	18, 27, 29, 37
		liter (symbols)	37
candela	5, 31, 36	lumen	19
candle, new	19, 32		
Committee, International, for Weights and Measures (CIPM)	44-46		
Committees, Consultative	45		
Conference, General, on Weights and Measures (CGPM)	44-46	mass	40
Convention, Meter	44	mass and weight	18
coulomb	20	meter	3, 17, 19, 25
cubic decimeter	27	micron	32
curie	29	mole	4, 34
		newton	19
definitions of units, practical realization of the degree Celsius	39-43 4, 21, 30	numbers, writing and printing of	22
		ohm	20
electric quantities	41		
exa	36		
		pascal	33
		peta	36
farad	20	photometric quantities	43
femto	29	prefixes, SI	11, 26, 29, 36
frequency standard (^{133}Cs)	28	prefixes, SI, rules for use of	11
		quantities, system of	2
g_n	18	quantity, meaning of	6
gray	35		
		radian	9, 26
		realization, practical, of the definitions of some important units	39-43
henry	20		

	Page		Page
second	3, 24, 25, 30	unit of quantity of heat (joule)	20
SI units and multiples thereof	26, 33	units in use temporarily	14
siemens	33	units, CGS, with special names	15
sievert	37	units, electric	19
steradian	9, 26	units generally deprecated	16
substance, amount of	4, 34	units in use with SI	13
symbols, for base units	6	units, legislation on	2
symbols, for derived units with special names	7	units, photometric	19
symbols, for the liter	13, 37	units, SI base	3
symbols, writing & use of	6, 10, 22	units, SI base, symbols	6
system of quantities	2	units, SI derived	6-8, 27, 32
system of units, international	26	units, SI derived, with special names	7
system of units, proposal for		units, SI, multiples and submultiples of	2, 11
establishing a practical	21, 23, 24	units, SI supplementary	9, 38
		units, SI, the three classes of, UTC	1 35
TAI	33		
temperature	41	volt	20
temperature, Celsius	4		
temperature, thermodynamic	4, 30		
thermodynamic scale	20, 23		
time	40	watt	20
time, international atomic	33-34	weber	20
time, universal coordinated	35	weight (<i>see</i> mass)	

NBS TECHNICAL PUBLICATIONS

PERIODICALS

JOURNAL OF RESEARCH—The Journal of Research of the National Bureau of Standards reports NBS research and development in those disciplines of the physical and engineering sciences in which the Bureau is active. These include physics, chemistry, engineering, mathematics, and computer sciences. Papers cover a broad range of subjects, with major emphasis on measurement methodology and the basic technology underlying standardization. Also included from time to time are survey articles on topics closely related to the Bureau's technical and scientific programs. As a special service to subscribers each issue contains complete citations to all recent Bureau publications in both NBS and non-NBS media. Issued six times a year. Annual subscription: domestic \$16; foreign \$20. Single copy, \$3.75 domestic; \$4.70 foreign.

NOTE: The Journal was formerly published in two sections: Section A "Physics and Chemistry" and Section B "Mathematical Sciences."

DIMENSIONS/NBS—This monthly magazine is published to inform scientists, engineers, business and industry leaders, teachers, students, and consumers of the latest advances in science and technology, with primary emphasis on work at NBS. The magazine highlights and reviews such issues as energy research, fire protection, building technology, metric conversion, pollution abatement, health and safety, and consumer product performance. In addition, it reports the results of Bureau programs in measurement standards and techniques, properties of matter and materials, engineering standards and services, instrumentation, and automatic data processing. Annual subscription: domestic \$11; foreign \$13.75.

NONPERIODICALS

Monographs—Major contributions to the technical literature on various subjects related to the Bureau's scientific and technical activities.

Handbooks—Recommended codes of engineering and industrial practice (including safety codes) developed in cooperation with interested industries, professional organizations, and regulatory bodies.

Special Publications—Include proceedings of conferences sponsored by NBS, NBS annual reports, and other special publications appropriate to this grouping such as wall charts, pocket cards, and bibliographies.

Applied Mathematics Series—Mathematical tables, manuals, and studies of special interest to physicists, engineers, chemists, biologists, mathematicians, computer programmers, and others engaged in scientific and technical work.

National Standard Reference Data Series—Provides quantitative data on the physical and chemical properties of materials, compiled from the world's literature and critically evaluated. Developed under a worldwide program coordinated by NBS under the authority of the National Standard Data Act (Public Law 90-396).

NOTE: The principal publication outlet for the foregoing data is the Journal of Physical and Chemical Reference Data (JPCRD) published quarterly for NBS by the American Chemical Society (ACS) and the American Institute of Physics (AIP). Subscriptions, reprints, and supplements available from ACS, 1155 Sixteenth St., NW, Washington, DC 20056.

Building Science Series—Disseminates technical information developed at the Bureau on building materials, components, systems, and whole structures. The series presents research results, test methods, and performance criteria related to the structural and environmental functions and the durability and safety characteristics of building elements and systems.

Technical Notes—Studies or reports which are complete in themselves but restrictive in their treatment of a subject. Analogous to monographs but not so comprehensive in scope or definitive in treatment of the subject area. Often serve as a vehicle for final reports of work performed at NBS under the sponsorship of other government agencies.

Voluntary Product Standards—Developed under procedures published by the Department of Commerce in Part 10, Title 15, of the Code of Federal Regulations. The standards establish nationally recognized requirements for products, and provide all concerned interests with a basis for common understanding of the characteristics of the products. NBS administers this program as a supplement to the activities of the private sector standardizing organizations.

Consumer Information Series—Practical information, based on NBS research and experience, covering areas of interest to the consumer. Easily understandable language and illustrations provide useful background knowledge for shopping in today's technological marketplace.

Order the above NBS publications from: Superintendent of Documents, Government Printing Office, Washington, DC 20402.

Order the following NBS publications—FIPS and NBSIR's—from the National Technical Information Services, Springfield, VA 22161.

Federal Information Processing Standards Publications (FIPS PUB)—Publications in this series collectively constitute the Federal Information Processing Standards Register. The Register serves as the official source of information in the Federal Government regarding standards issued by NBS pursuant to the Federal Property and Administrative Services Act of 1949 as amended, Public Law 89-306 (79 Stat. 1127), and as implemented by Executive Order 11717 (38 FR 12315, dated May 11, 1973) and Part 6 of Title 15 CFR (Code of Federal Regulations).

NBS Interagency Reports (NBSIR)—A special series of interim or final reports on work performed by NBS for outside sponsors (both government and non-government). In general, initial distribution is handled by the sponsor; public distribution is by the National Technical Information Services, Springfield, VA 22161, in paper copy or microfiche form.

**U.S. DEPARTMENT OF COMMERCE
National Bureau of Standards**

Washington, DC 20234

POSTAGE AND FEES PAID
U.S. DEPARTMENT OF COMMERCE
COM-215



OFFICIAL BUSINESS

Penalty for Private Use, \$300

THIRD CLASS